G301 Utility Water is found in several markets under different "aliases". Its excellent temperature range, weathering resistance, and economic price make it a popular choice for many applications, such as car heater hose and dishwasher drain hose. Utility Water is most often sold in precut lengths in boxes for easy storage and dispensing. However, it is also available in long lengths on reels.

G301... UTILITY WATER

Tube: Black, heat, and mild-chemical resistant EPDM rubber.

Reinforcement: Two spirals of synthetic spiralled yarn

Cover: Smooth, black, heat, abrasion and weather resistant

EPDM rubber.

Temperature Range: -40°C (-40°F) to 100°C (212°F) continu-

ous, 125°C (257°F) intermittent.



G311 & 322



			Working	Weight	PRICE PER FOOT		Approx
I.D.	Part Number	0.D.	Pressure	per ft	Cut	Reel	Reel Length
1/2"	G301-050	0.81"	50 psi	0.16 lb	\$1.35	\$1.15	700 ft
5/8	G301-063	0.88	35	0.20	1.50	1.26	700
3/4	G301-075	1.03	31	0.23	1.90	1.65	700
D d	1						

Boxed	Boxed Lengths						
I.D.	Length	Part Number	Weight Each	PRICE EACH			
1/2"	50 ft	G301-050X50FT	8.3 lb	\$57.50			
5/8	50	G301-063X50FT	10.3	63.00			
3/4	50	G301-075X50FT	11.8	82.50			

G311 and G322 Industrial Water are rugged hoses capable of handling most washdown and water conveying applications. While G311 offers a lightweight, two-spiral construction, G322 is a four-spiral hose for extra kink resistance and working pressure. These hoses are also used for low-pressure agricultural spray applications.

G311 & G322... INDUSTRIAL WATER

Tube: Black, heat, and mild-chemical resistant EPDM rubber. **Reinforcement:** Two or four spirals of synthetic spiralled yarn.

Cover: Smooth, black, heat, abrasion and weather resistant EPDM rubber.

Temperature Range: -40°C (-40°F) to 100°C (212°F)

I.D.	Part Number	0.D.	Working Pressure	Weight per ft	PRI Cut	CE PER 1500ft Box*		Approx Reel Length
1.0.	Humber	0.0.	TTC35uTC	регте	cut	130011 00x	NCCI	Rect Length
3/8"	G311-038	0.69"	200 psi	0.15 lb	\$1.35		\$1.05	700 ft
1/2	G311-050	0.81	150	0.19	1.40		1.26	700
5/8	G311-063	0.93	150	0.23	1.75	\$1.53	1.40	750
3/4	G311-075	1.15	150	0.33	2.10		1.90	700
1	G311-100	1.37	150	0.41	3.30		2.80	700
3/4	G322-075	1.15	300	0.40	3.30		2.30	700
1	G322-100	1.37	200	0.49	3.60		3.00	700
1 1/4	G322-125	1.75	200	0.79	6.90		5.60	500
1 1/2	G322-150	2.00	200	0.90	7.80		7.10	400

*Note: The 1500 ft box is a continuous length with both ends available for easy fitting attachment.