



Main

Product or component type	Motor starter
Type	S
Control Circuit Type	Common control circuit

Complementary

Control Circuit Voltage	220 V AC 50 Hz 240 V AC 60 Hz
Motor starter type	Non reversing
Current Rating	9 A
Number of Poles	2P
Number of Phases	1 phase
Horsepower Rating	0.33 HP 115 V AC 1 HP 230 V AC
Maximum Voltage Rating	600 V AC
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Without
Product compatibility	Circuit-breaker: 5 kA at 600 V AC Fuse: 5 kA at 600 V AC
Thermal overload type	Melting alloy 1
Electrical connection	Screw clamp terminals
NEMA size	00
Height	10.00 in (254 mm)
Depth	5.55 in (141 mm)
Maximum Width	5.98 in (152 mm)

Environment

Enclosure Type	NEMA 1 painted sheet steel
Product certifications	UL Listed CSA NEMA

Ordering and shipping details

Category	21191 - 8502,36 SA,SB(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	00785901080381
Nbr. of units in pkg.	1
Package weight(Lbs)	7.2 lb(US) (3.27 kg)
Returnability	No
Country of origin	MX

Packing Units

Package 1 Height	6.50 in (16.510 cm)
Package 1 width	6.50 in (16.510 cm)
Package 1 Length	10.60 in (26.924 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	China RoHS Declaration
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------