



### Main

|                                       |                                 |
|---------------------------------------|---------------------------------|
| Range of product                      | OsiSense XU                     |
| Accessory / separate part category    | Fuses                           |
| Accessory / separate part type        | Fast blow fuse                  |
| Accessory / separate part designation | Cartridge fuse                  |
| Accessory / separate part destination | Unprotected 2-wire AC/DC sensor |
| Sale per indivisible quantity         | 10                              |

### Complementary

|                       |                        |
|-----------------------|------------------------|
| Product compatibility | XT<br>XS               |
| [In] rated current    | 0.8 A                  |
| Fuse size             | 5 x 20 mm              |
| Fuse curve            | Fast blow              |
| Local signalling      | Without                |
| Net weight            | 0.00 lb(US) (0.001 kg) |

### Packing Units

|                  |                        |
|------------------|------------------------|
| Package 1 Weight | 0.00 lb(US) (0.001 kg) |
| Package 1 Height | 0.050 dm               |
| Package 1 width  | 0.700 dm               |
| Package 1 Length | 0.400 dm               |

### Offer Sustainability

|                          |   |
|--------------------------|---|
| REACH Regulation         | <a href="#">REACH Declaration</a>             |
| EU RoHS Directive        | Not applicable, out of EU RoHS legal scope    |
| Environmental Disclosure | <a href="#">Product Environmental Profile</a> |
| Circularity Profile      | <a href="#">End of Life Information</a>       |

Contractual warranty

---

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

---