



Main

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCE
Head type	Plunger head
Product compatibility	XCKP XCKD XCMD XCKT
Associated body	ZCT26P16 ZCD37 ZCP21M12 ZCD29M12 ZCT27G11 ZCMD29L5 ZCMD41L2 ZCD31 ZCMD21L1 ZCT21P16 ZCT25N12 ZCMD21L08R12 ZCD35 ZCMD81L2 ZCT28G11 ZCMD39L2 ZCMD69C12 ZCMD39L5 ZCD25 ZCMD61C12 ZCD21M12 ZCT27N12 ZCD26 ZCP29M12 ZCMD21M12 ZCMD25L5 ZCMD81L5 ZCT25G11

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

ZCMD29C12
 ZCMD25L2
 ZCMD29L1
 ZCMD21L08U78
 ZCP31
 ZCT26G11
 ZCMD61M12
 ZCMD41L5
 ZCMD21C12
 ZCMD41L1
 ZCMD21L2
 ZCP39
 ZCD27
 ZCP25
 ZCD28
 ZCP29
 ZCT27P16
 ZCMD29L2
 ZCMD37L5
 ZCD29
 ZCT26N12
 ZCT28N12
 ZCD39
 ZCMD37L1
 ZCP26
 ZCMD39L1
 ZCMD37L2
 ZCP37
 ZCP35
 ZCT21G11
 ZCD21
 ZCP27
 ZCMD81L1
 ZCT28P16
 ZCT21N12
 ZCP28
 ZCMD25L1
 ZCMD21L5
 ZCT25P16
 ZCP21

Movement of operating head	Linear
Type of operator	End plunger spring return metal
Type of approach	Vertical approach, 1 direction

Complementary

Positive opening	With
------------------	------

Environment

Ambient air temperature for operation	-13...158 °F (-25...70 °C)
Ambient air temperature for storage	-40...158 °F (-40...70 °C)
Environmental characteristic	Standard environment

Packing Units

Package 1 Weight	0.02 lb(US) (0.010 kg)
Package 1 Height	0.150 dm
Package 1 width	0.300 dm
Package 1 Length	0.250 dm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes

RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
