

Product Datasheet

Characteristic

9070T5000D1

TRANSFORMER CONTROL 5000VA 240/480V-120V



Main

product or component type	Industrial Control Transformer
rated power in VA	5000 VA
primary voltage	220 x 440 V 230 x 460 V 240 x 480 V
secondary voltage	115 V 120 V 110 V
range of product	T

Complementary

Phase	1 phase
rated power in VA	5000 VA UL 5000 VA CSA 5000 VA NOM 3000 VA CE
primary voltage	220 x 440 V 110 V 230 x 460 V 115 V 240 x 480 V 120 V
temperature rise	115 °C
electrical connection	Screw clamp terminals
height	8.75 in (222.25 mm)
width	228.60 mm (9 in)
depth	232.41 mm (9.15 in)
material	Copper winding
product compatibility	FSC2

Environment

product certifications	CSA file LR37055 guide 184-N-90 CE UL listed file E61239
NEMA degree of protection	Not rated (open device)
insulation temperature	356 °F (180 °C)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	Free of Substances of Very High Concern above the threshold
REACH free of SVHC	Yes
EU RoHS Directive	Compliant
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	ENVPEP1308008EN
Circularity Profile	N/A