

Product data sheet

Characteristics

CQO24L60NRNM

Loadcentre enclosure, QO, 1 phase, 2 spaces, 4 circuits, 60A bus rating, NEMA3R, nonmetallic



Main

Marketing Trade Name	QO
Product	Load Center Enclosure
Enclosure Type	Weatherproof enclosure

Complementary

Tightening Torque	Main lugs 35 lb.in, AWG 14...AWG 10, aluminium/copper Main lugs 45 lb.in, AWG 3, aluminium/copper Main lugs 40 lb.in, AWG 8...AWG 4, aluminium/copper Main lugs 35 lb.in, AWG 12...AWG10, aluminium/copper
Load Center Type	Main breaker
Number of Spaces	2
Max Short Circuit Current Rating	65 kA
Maximum Number of Single Pole Circuits	4
Maximum Number of Tandem Breakers	4
Number of Phases	1 phase
Voltage Rating	120/240 V AC
Wire Size	AWG 14...AWG 4 aluminium/copper
Electrical Connection	Lugs
Grounding Bar	Grounding bar (factory installed)
Electrical Connection	Lugs
Wiring Configuration	3-wire
Box Number	1NM
Height	9.65 in (245 mm)
Width	6.40 in (162.5 mm)
Depth	3.74 in (95 mm)

Environment

Enclosure Rating	NEMA 3R outdoor
Product Certifications	CSA UL Listed

Ordering and shipping details

Category	01081 - INTRA-COMPANY COMPONENTS
Discount Schedule	NET
GTIN	00785901294597
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	4.00 in (10.16 cm)
Package 1 width	6.50 in (16.51 cm)
Package 1 Length	9.30 in (23.622 cm)
Package 2 Weight	15.34 lb(US) (6.958 kg)

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration