

Product Datasheet

Characteristic

LR3D10

TeSys LRD thermal overload relays - 4...
6 A - class 10A



Main

range	TeSys
product name	TeSys LRD
product or component type	non differential thermal overload relay
device short name	LR3D
relay application	motor protection
product compatibility	LC1D09 LC1D12 LC1D18 LC1D25 LC1D32 LC1D38
network type	AC DC
thermal protection adjustment range	4...6 A
[Ui] rated insulation voltage	600 V power circuit conforming to CSA 600 V power circuit conforming to UL 690 V power circuit conforming to IEC 60947-4-1

Complementary

network frequency	0...400 Hz
mounting support	plate with specific accessories rail with specific accessories under contactor
tripping threshold	1.14 +/- 0.06 I _r (conforming to IEC 60947-4-1)
[I _{th}] conventional free air thermal current	5 A for signalling circuit
permissible current	3 A at 120 V AC-15 for signalling circuit 0.22 A at 125 V DC-13 for signalling circuit
System Voltage	690 V AC 0...400 Hz
[U _{imp}] rated impulse withstand voltage	6 kV
phase failure sensitivity	tripping current 130 % of I _r on two phase, the last one at 0
control type	red push-button stop blue push-button for reset mode
temperature compensation	-4...140 °F (-20...60 °C)
connections - terminals	control circuit: screw clamp terminals 2 cable(s) 0...0 in ² (1...2.5 mm ²) - cable stiffness: flexible - without cable end control circuit: screw clamp terminals 2 cable(s) 0...0 in ² (1...2.5 mm ²) - cable stiffness: flexible - with cable end control circuit: screw clamp terminals 2 cable(s) 0...0 in ² (1...2.5 mm ²) - cable stiffness: flexible - with cable end

	mm ²) - cable stiffness: solid - without cable end power circuit: screw clamp terminals 1 cable(s) 0...0.02 in ² (1.5...10 mm ²) - cable stiffness: flexible - without cable end power circuit: screw clamp terminals 1 cable(s) 0...0.01 in ² (1...4 mm ²) - cable stiffness: flexible - with cable end power circuit: screw clamp terminals 1 cable(s) 0...0.01 in ² (1...6 mm ²) - cable stiffness: solid - without cable end
tightening torque	control circuit: 15.04 lbf.in (1.7 N.m) - on screw clamp terminals power circuit: 15.04 lbf.in (1.7 N.m) - on screw clamp terminals
width	1.77 in (45 mm)
depth	2.76 in (70 mm)
product weight	0.27 lb(US) (0.124 kg)
compatibility code	LR3D

Environment

protective treatment	TH (conforming to IEC 60068)
IP degree of protection	IP20 (conforming to IEC 60529)
ambient air temperature for operation	without derating conforming to IEC 60947-4-1
ambient air temperature for storage	-76...158 °F (-60...70 °C)
flame retardance	V1 (conforming to UL 94)
mechanical robustness	vibrations: 6 Gn IEC 60068-2-6 shocks 15 Gn for 11 ms IEC 60068-2-7
dielectric strength	6 kVat 50 Hz conforming to IEC 60255-5
standards	ATEX D 94/9/CE EN 60947-4-1 EN 60947-5-1 IEC 60947-4-1 IEC 60947-5-1 UL 508 CSA C22.2 No 14
product certifications	ATEX INERIS BV CCC CSA DNV GL GOST LROS (Lloyds register of shipping) RINA UL