



Overview

Lead time	Usually in Stock
-----------	------------------

General

Provided Equipment	Installation guide
--------------------	--------------------

Physical

Depth	7.01 in (17.8 cm)
Height	4.02 in (10.2 cm)
Product Weight	2.49 lb(US) (1.13 kg)
Width	7.99 in (20.3 cm)

Environmental

Ambient Air Temperature for Operation	32...113 °F (0...45 °C)
Operating altitude	0...10000 ft
Relative Humidity	0...95 %
Ambient Air Temperature for Storage	5...149 °F (-15...65 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)
Storage Relative Humidity	0...95 %

Ordering and shipping details

GTIN	00731304332077
Package weight(Lbs)	2.76 lb(US) (1.25 kg)

Packing Units

Package 1 Height	8.15 in (20.7 cm)
Package 1 width	8.27 in (21 cm)
Package 1 Length	10.00 in (25.4 cm)

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
-------------------	---

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.