

CH364VW

200A 3P Type1 600V Heavy Duty Fusible Safety Switch With Viewing Window



Main

Product	Single Throw Safety Switch
Disconnect Type	Fusible disconnect
Number of Poles	3
Electrical Connection	Lugs
Duty Rating	Heavy duty

Complementary

Line Rated Current	200 A
Factory Installed Neutral	None
Mounting Type	Surface
Voltage Rating	600 V AC/DC
Wire Size	AWG 6...250 kcmil copper or aluminum
Motor power hp	50 hp 480 V AC 50...60 Hz 3 phases NEC 240.6 125 hp 480 V AC 50...60 Hz 3 phases NEC 430.52 60 hp 600 V AC 50...60 Hz 3 phases NEC 240.6 150 hp 600 V AC 50...60 Hz 3 phases NEC 430.52 40 hp 250 V DC 50 hp at 600 V DC
Height	29 in (736.60 mm)
Width	18.5 in (469.90 mm)
Depth	8.25 in (209.55 mm)
Tightening torque	275 lbf.in (31.07 N.m) 0.02...0.20 in ² (13.30...127 mm ²) AWG 6...250 kcmil)

Environment

Certifications	CSA
Enclosure Rating	NEMA 1 galvanized steel

Packing Units

Package 1 Weight	45.00 lb(US) (20.412 kg)
------------------	--------------------------

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
PVC free	Yes