



Cable Shears with twin cutting edge



95 11 200 

tool burnished, plastic-coated handles



95 12 200 

tool burnished, handles with multi-component covers



- Description
- Special
- Applications
- for cutting copper and aluminium cables
- not suitable for steel wire and hard drawn copper conductors
- precision ground, hardened blades
- clean and smooth cut without crushing and deformation
- by dividing the cutting actions into initial cut (insulating sheath in the front cutting area) and final cut (conductor in the back cutting area), cables up to $\text{Ø } 51/64''$ (20 mm) can be cut in one-hand operation
- less effort required due to favourable lever ratio and optimised cutting-edge geometry
- pinch guard prevents operators' fingers being pinched
- adjustable bolted joint, self-locking
- High-grade special tool steel; forged, oil-hardened

The double cutting edge allows a comfortable handle position in all cutting situations inside the specified cutting capacity.









Initial cut: Using the front cutting edge to cut the insulating sheath on larger cable diameters leaves an ergonomic handle opening width.



Final cut: After cutting the sheath in the front profile the conductors in the rear part are cut. Initial cut in the front profile, final cut in the rear profile - to keep it as easy as possible.

Product Number	EAN 4003773-	 Ø mm	 mm ²	AWG	 mm	 g
95 11 200	043928	20,00	70,00	2/0	200	283
95 12 200	047834	20,00	70,00	2/0	200	324

technical change and errors excepted