



Overview

Presentation	Universal Sensor that monitors access to NetShelter SX Enclosures.
Lead time	Usually Ships within 2 Weeks

General

Provided Equipment	Cable ties
Display Resolution	Up to 640x480
External Sensor Connection Type	Alarm Beacon 1 PS2 mini-DIN
APC Universal Sensors Supported	Door contact Humidity Smoke Temperature
Number of Universal Sensor Ports	2
Number of Sensor Pods Supported	0
Number of Universal Sensors Supported	0
Sensor Humidity Range	10...90 % +/- 5 % non-condensing RH
Number of Cameras Supported	4 Networked 4
Sensor Temperature Range	1.6...48.8 °C +/- 1 °C 35...120 °F

Physical

Depth	7.36 in (18.7 cm)
Height	0.75 in (1.9 cm)
Product Weight	0.82 lb(US) (0.37 kg)
Width	5.75 in (14.6 cm)

Output

Number of port	0
----------------	---

Environmental

Ambient Air Temperature for Operation	32...113 °F (0...45 °C)
Operating altitude	0...10000 ft
Relative Humidity	0...95 %
Ambient Air Temperature for Storage	5...149 °F (-15...65 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)
Storage Relative Humidity	0...95 %

Ordering and shipping details

GTIN	00731304262855
Package weight(Lbs)	1.08 lb(US) (0.49 kg)

Packing Units

Package 1 Height	1.89 in (4.8 cm)
Package 1 width	9.13 in (23.2 cm)
Package 1 Length	6.46 in (16.4 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Compliant EU RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------