



Environment

NEMA degree of protection	NEMA 4X indoor UL 508
Protective treatment	TC
Ambient air temperature for storage	-40...70 °C

Physical characteristics

Material	Glass reinforced polyamide base unit
Mounting diameter	70 mm
Product weight	0,16 kg

Functional

Assembly style	Customer assembly, up to 5 units
Terminals description ISO n°1	(COM-1)PW (COM-2)PW (COM-3)PW (COM-4)PW (COM-5)PW (GND)GROUND

Connections

Cable entry	Bottom or side entry
-------------	----------------------

Certifications and standards

Product certifications	CCC CSA C22-2 No 14 GOST UL 508
Standards	EN/IEC 60947-5-1

Product identification

Component name	XVBC
Indicator bank base type	Standard
Product or component type	Base unit
Range of product	Harmony XVB Universal

Installation

Fixing mode	Direct or tube fixing
-------------	-----------------------

Compatibility

Product destination	Banks without flash discharge tube unit
---------------------	---

Complementary description

Range ID	644
RoHS EUR conformity date	0808
RoHS EUR status	Compliant
Former Brand	Telemecanique

Main characteristics

Common description	Base unit for bank XVB - with 'flash' discharge tube - black - IP 65
Commercial Reference	XVBC07
EAN Number	3389110845037
Product GDP Code	4317
Short description	BASE UNIT FOR BANK XVB WITH FLASH DISC
Brand	Telemecanique
Current cross distribution chain status	08 - Commercialised

Logistic

Business material type	Referenced Product
Minimum sales order quantity	1
Basic packaging quantity	1

Pricing

Reference price	0,00
Price per	0
Price unit	ST - Piece

Management information

Creation date	18/02/2007
First global validation date	09/10/2008
GMR last update date	10/06/2009
Product part number	XVBC07
Project reference	XVBC07
Effect. date next global CDC	27/11/2006
Last update date	29/08/2009
Released for	All

Weight and dimensions

First packaging gross weight	0,177 kg
First packaging gross height	1 dm
First packaging gross length	1 dm
Bare product net height	0,08 m
Bare product net length	0,095 m
Bare product net weight	0,177 kg
Bare product net width	0,08 m
First packaging gross width	1,2 dm