
 TECHNICAL DATA SHEET

Liquid-tight fittings - Series 5300SST6

For liquid-tight flexible metallic conduit

T&B Liquidtight Systems®



Stainless steel 316 liquid-tight and system solutions for the most demanding corrosive environments

Certifications / Standards:



Features & Benefits:

- Meets UL 514B and CSA C22.2 No. 18.3 for liquid-tight fittings
- Full compliance to IEC 61386-1, -23 requirements
- NPT Thread Fittings are compliant with NSF/ANSI 169 requirements for non-food and splash zone application.
- Trade sizes from 3/8" to 2" (12mm to 63mm)
- Insulated throat helps protect wire jacket from damage
- Straight, 45° and 90° conduit bodies
- NPT and ISO Metric Thread Types
- Coordinated performance with T&B Liquidtight Systems Flexible Metallic Conduits
- Ingress protection ratings aligned with industrial enclosures
- Safe-Edge® ground cones help provide superior bonding
- Double Bevel Sealing Ring eases assembly and helps ensure liquid-tight performance
- Heat curled insulators protect wire sheathing from damage

Applications:

- Typical applications where severe corrosion protection is required including water/wastewater, food & beverage, salt environments, chemical processing, etc.
- Used where liquid tight flexible metallic raceway is installed in corrosive outdoor or indoor locations, and exposed to continuous or intermittent moisture
- Used to positively bond flexible liquid-tight flexible metallic conduit to boxes or enclosures
- Ideal for use with T&B Liquidtight Systems LFMC types LT4GE, LT6GE and LT6FE
- Liquid-tight applications against water, oils, cutting fluids, mild acids
- For use in electrical circuits up to 1,000 V
- Suitable for use in Class I Division 2, Class II Division 1 & 2 Hazardous Locations per NEC® Section 500

Construction / Material / Finish:

- Trade sizes 3/8" to 2" Steel Steel 316
- Zinc Plated steel ground cones, optional stainless steel 316
- Thermoplastic nylon seal rings and insulators
- Halogen Free seal rings, insulators and seal gaskets
- Machined locknuts with teeth for vibration resistance, supplied separately

Environment ratings:

Working Temperature:

- UL: Gen: -20 to +105°C (-4 to +221°F)
- CSA: Gen: -20 to +105°C (-4 to +221°F)
- IEC/CE: Gen: -45 to +150°C (-49 to +302°F) Static
Gen: -25 to +105°C (-13 to +221°F) Dynamic

Chemical Resistance Guide:

- See Publication TDS000081 (Fittings: Stainless Steel 316 & PA66 Polyamide)
- See Publication TDS000117 (Liquid Tight Flexible Metal Conduits)

Conforms to:

- UL 514B, Fittings for Cable and Conduit
 - E23018 (-6 SST Ground Cone: 1/2" and 3/4" only)
- CSA C22.2 No. 18.3, Outlet and Conduit Boxes, Fittings and Accessories
 - File: LR-4484
- IEC/EN 61386-1, -23, Conduit Systems for Cable Management
 - EU DoC: EC-012-7189
- RoHS (Restriction of Hazardous Substance directive)
- NEMA FB-1 (Fittings and Conduit Bodies)
- JIC EGP1 (Electrical standard for GP machine tools)
- JIC EMP1 (Electrical Standard for Mass Production Engineering)
- Federal Specification A-A 50552 (Fittings for flexible conduit)
- Federal Specification H-28 (Threads)
- NSF/ANSI 169 - Special Purpose Food and Beverage Devices
 - File: 82050

Ingress Protection:

- Helps provide "Ingress Integrity" between enclosures, fittings, conduits & seals when using Series 5300SST6 liquid-tight fittings and T&B Liquidtight Systems LFMC
- Covers all trade sizes from 3/8" to 2" (12mm to 63mm)
- Ingress ratings require use of Series 5260 Seal Gaskets
- ISO Metric Thread fittings supplied with Seal O-Rings as standard

UL, CSA & NEMA system ingress ratings:

- UL Listed type ratings tested to UL 50/50E requirements with UL Listed LFMC
- UL File No.: E23018
 - Indoor: Type 4, 4X, 6, 12, 13
 - Outdoor: Type 3, 3R, 4, 4X, 6
- CSA C22.2 No. 94.2: Type 3, 3R, 4, 4X, 12, 13
- NEMA 250: Type 3, 3R, 4, 4X, 12, 13

IEC system ingress ratings:

- IP Ingress Protection per IEC 60529 requirements
- IEC Ingress Ratings: IP66, IP67, IP68, IP69

Standards requirements:

Designed to UL 514B and CSA C22.2 No. 18.3 test requirements including:

- Assembly, Pull, Resistance, Oil spray, Polymer durability, Flammability Coating thickness, Current withstand

Meets all IEC/EN 61386-1, -23 standard requirements including:

- Impact resistance - Code 3 Medium; 6 Joules
- Tensile strength - Code 3 Medium; 500 N/2 min.
- Lower and upper temperatures
- IP protection against solid and liquids

Product selection											
Series 5300SST6 Liquid-tight Fittings											Seal Gaskets
Trade size			Thread Type		Insulated with steel ground cone			Insulated with SST 316 ground cone			Part no.
					Straight	45°	90°	Straight	45°	90°	
Inches	Metric	ISO BS EN	Std	Size	Part no.	Part no.	Part no.	Part no.	Part no.	Part no.	Part no.
3/8"	12mm	16mm	NPT	3/8"	5331SST6	5341SST6	5351SST6	5331SST6-6	5341SST6-6	5351SST6-6	5261
			ISO	M16	9330SST6	9340SST6	9350SST6	9330SST6-6	9340SST6-6	9350SST6-6	—
1/2"	16mm	20mm	NPT	1/2"	5332SST6	5342SST6	5352SST6	5332SST6-6	5342SST6-6	5352SST6-6	5262
			ISO	M20	9332SST6	9342SST6	9352SST6	9332SST6-6	9342SST6-6	9352SST6-6	—
3/4"	21mm	25mm	NPT	3/4"	5333SST6	5343SST6	5353SST6	5333SST6-6	5343SST6-6	5353SST6-6	5263
			ISO	M25	9333SST6	9343SST6	9353SST6	9333SST6-6	9343SST6-6	9353SST6-6	—
1"	27mm	32mm	NPT	1"	5334SST6	5344SST6	5354SST6	5334SST6-6	5344SST6-6	5354SST6-6	5264
			ISO	M32	9334SST6	9344SST6	9354SST6	9334SST6-6	9344SST6-6	9354SST6-6	—
1 1/4"	35mm	40mm	NPT	1-1/4"	5335SST6	5345SST6	5355SST6	5335SST6-6	5345SST6-6	5355SST6-6	5265
			ISO	M40	9335SST6	9345SST6	9355SST6	9335SST6-6	9345SST6-6	9355SST6-6	—
1 1/2"	41mm	50mm	NPT	1-1/2"	5336SST6	5346SST6	5356SST6	5336SST6-6	5346SST6-6	5356SST6-6	5266
			ISO	M50	9336SST6	9346SST6	9356SST6	9336SST6-6	9346SST6-6	9356SST6-6	—
2"	53mm	63mm	NPT	2"	5337SST6	5347SST6	5357SST6	5337SST6-6	5347SST6-6	5357SST6-6	5267
			ISO	M63	9337SST6	9347SST6	9357SST6	9337SST6-6	9347SST6-6	9357SST6-6	—

Note: ISO Metric thread fittings supplied with Seal O-Rings as standard.

Dimensions (approximate)

Drawing	Trade size			Inches			Millimeters			Weight	
	Inches	Metric	ISO BS EN	A	B	C	A	B	C	lbs.	kg
Series 5300SST6 Straight LT Fittings - NPT Threads											
	3/8"	12mm	16mm	1 1/8"	1"	3/2"	28.5	25.4	12.7	0.11	0.05
	1/2"	16mm	20mm	1 9/16"	1"	9/16"	32.6	25.4	14.3	0.19	0.08
	3/4"	21mm	25mm	1 9/16"	1 1/16"	9/16"	40.5	27.0	14.3	0.27	0.12
	1"	27mm	32mm	1 3/4"	1 1/16"	3/4"	46.5	33.3	19.1	0.41	0.19
	1 1/4"	35mm	40mm	2 13/16"	1 11/16"	13/16"	56.2	42.9	20.6	0.73	0.33
	1 1/2"	41mm	50mm	2 1/2"	1 7/8"	13/16"	63.7	47.6	20.6	0.85	0.39
	2"	53mm	63mm	3"	2 3/16"	7/8"	76.6	55.6	22.2	1.11	0.51
	2 1/2"	63mm	70mm	—	—	—	—	—	—	—	—
	3"	78mm	80mm	—	—	—	—	—	—	—	—
	4"	103mm	100mm	—	—	—	—	—	—	—	—
Series 5300SST6 45° LT Fittings - NPT Threads											
	3/8"	12mm	16mm	1 1/8"	1 1/16"	3/2"	28.5	39.7	12.7	0.20	0.09
	1/2"	16mm	20mm	1 9/16"	1 7/8"	9/16"	32.6	43.0	14.3	0.25	0.11
	3/4"	21mm	25mm	1 9/16"	2 1/8"	9/16"	40.5	54.0	14.3	0.35	0.16
	1"	27mm	32mm	1 3/4"	2 1/4"	3/4"	46.5	57.2	19.1	0.64	0.29
	1 1/4"	35mm	40mm	2 13/16"	2 3/4"	13/16"	56.2	69.9	20.6	0.86	0.39
	1 1/2"	41mm	50mm	2 1/2"	3 3/8"	13/16"	63.7	85.7	20.6	1.19	0.54
	2"	53mm	63mm	3"	3 7/8"	7/8"	76.6	98.4	22.2	2.68	1.22
	2 1/2"	63mm	70mm	—	—	—	—	—	—	—	—
	3"	78mm	80mm	—	—	—	—	—	—	—	—
	4"	103mm	100mm	—	—	—	—	—	—	—	—
Series 5300SST6 90° LT Fittings - NPT Threads											
	3/8"	12mm	16mm	1 1/8"	1 3/8"	3/2"	28.5	34.9	12.7	0.21	0.10
	1/2"	16mm	20mm	1 9/16"	1 9/16"	9/16"	32.6	39.7	14.3	0.37	0.17
	3/4"	21mm	25mm	1 9/16"	1 3/4"	9/16"	40.5	44.5	14.3	0.52	0.24
	1"	27mm	32mm	1 3/4"	2 3/16"	3/4"	46.5	55.6	19.1	0.79	0.36
	1 1/4"	35mm	40mm	2 13/16"	2 3/4"	13/16"	56.2	69.9	20.6	1.26	0.57
	1 1/2"	41mm	50mm	2 1/2"	2 15/16"	13/16"	63.7	74.6	20.6	1.75	0.79
	2"	53mm	63mm	3"	3 7/16"	7/8"	76.6	87.3	22.2	3.30	1.50
	2 1/2"	63mm	70mm	—	—	—	—	—	—	—	—
	3"	78mm	80mm	—	—	—	—	—	—	—	—
	4"	103mm	100mm	—	—	—	—	—	—	—	—

Note:
 • Dimensions for reference only.
 • Product must be installed in accordance with applicable national and local electrical codes.

tnb.abb.com (US/Latin America)
 tnb.ca.abb.com (Canada)
 abb.com

We reserve the right to make technical changes or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB does not accept any responsibility whatsoever for potential errors or possible lack of information in this document.

We reserve all rights in this document and in the subject matter and illustrations contained therein. Any reproduction – in whole or in part – is forbidden without prior written consent of ABB.
 © 2020 ABB Installation Products Inc. and/or its related companies. All Rights Reserved.