

Product data sheet

Characteristics

8903SQO2V02

Contactor, Type S, multipole lighting, electrically held, 100A, 3 pole, 120/100 VAC 60/50 Hz coil, open style



Main

| | |
|---------|--------------------------------------|
| Product | Electrically Held Lighting Contactor |
| Type | S |

Complementary

| | |
|-------------------------|----------------------------------|
| Control Circuit Voltage | 120 V AC 60 Hz 110 V AC 50 Hz |
| Current Rating | 100 A |
| Number of Poles | 3P |
| Control Units | No control units |
| Pilot Light | Without pilot light |
| Auxiliary Contacts | Without |
| Other Options | None |
| Electrical connection | Lugs |
| Height | 7.24 in (184 mm) |
| Depth | 6.50 in (165 mm) |
| Maximum Width | 5.43 in (138 mm) |

Environment

| | |
|------------------------|--------------------------------------|
| Enclosure Type | Not rated (open device) surface none |
| Product certifications | UL Listed CSA |

Ordering and shipping details

| | |
|-----------------------|---------------------------------|
| Category | 21325 - 8903 S (NOT S°C) ELECT. |
| Discount Schedule | CP1 |
| GTIN | 00785901619420 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 12.91 lb(US) (5.86 kg) |
| Returnability | Yes |
| Country of origin | MX |

Packing Units

| | |
|------------------|----------------------|
| Package 1 Height | 7.40 in (18.796 cm) |
| Package 1 width | 8.80 in (22.352 cm) |
| Package 1 Length | 14.30 in (36.322 cm) |

Offer Sustainability

| | |
|-----------------------|--|
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Not compliant |
| China RoHS Regulation | China RoHS Declaration |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|