



## Aluminum and Copper Neutral Bars Types NA and NC

**NEW  
PRODUCT**

- Aluminum Neutral Bars are manufactured from high strength aluminum alloy
- Copper Neutral Bars are manufactured from high strength copper
- For use in a variety of neutral and grounding applications
- Aluminum Neutral Bars are tin plated
- Screws are made of mild steel and plated
- Aluminum Neutral Bars are dual rated for copper or aluminum conductors
- Copper Neutral Bars are for copper conductors only
- UL 467 listed



### Aluminum Neutral Bars

CATALOG NUMBER	CONDUCTOR RANGE	NUMBER OF CIRCUITS	TOTAL NUMBER OF HOLES	APPROXIMATE DIMENSIONS (IN.)			HOLE SPACING	MOUNTING HOLE POSITION
				L	W	H		
NA-401	14 - 4	2	3	.95	.31	.44	.31	2
NA-402		4	5	1.57	.31	.44	.31	3
NA-403		5	6	1.88	.31	.44	.31	3
NA-404		6	7	2.25	.31	.44	.31	4
NA-405		4	6	1.88	.31	.44	.31	1 & 4
NA-406		5	7	2.25	.31	.44	.31	1 & 7
NA-407		5	7	2.25	.31	.44	.31	2 & 6
NA-408		6	8	2.56	.31	.44	.31	4 & 7
NA-409		7	9	2.87	.31	.44	.31	3 & 7
NA-410		9	11	3.50	.31	.44	.31	1 & 11
NA-411		10	12	3.81	.31	.44	.31	1 & 12
NA-412		12	14	4.43	.31	.44	.31	1 & 14
NA-413		15	17	5.37	.31	.44	.31	1 & 17
NA-414		20	22	6.93	.31	.44	.31	1 & 22
NA-415	190	190	60.00	.31	.44	.31	-	
NA-416	14 - 2	10	12	4.12	.38	.50	.34	3 & 11
NA-417	14 - 2/0	2	3	1.75	.56	.75	.60	2
NA-418		3	5	2.95	.56	.75	.60	2 & 4
NA-419		6	8	4.75	.56	.75	.60	1 & 8

### Copper Neutral Bars

CATALOG NUMBER	CONDUCTOR RANGE	NUMBER OF CIRCUITS	TOTAL NUMBER OF HOLES	APPROXIMATE DIMENSIONS			HOLE SPACING	MOUNTING HOLE POSITION
				L	W	H		
NC-420	14 - 4	4	6	1.94	.31	.44	.31	1 & 6
NC-421		5	7	2.25	.31	.44	.31	1 & 7
NC-422		6	8	2.56	.31	.44	.31	1 & 8
NC-423		12	14	4.43	.31	.44	.31	1 & 14
NC-424		13	15	4.74	.31	.44	.31	3 & 13
NC-425		13	15	4.74	.31	.44	.31	6 & 11
NC-426	190	190	60.00	.31	.44	.31	-	
NC-427	14 - 2	3	5	2.00	.38	.50	.40	1 & 5
NC-428		6	8	3.25	.38	.50	.40	2 & 7

