



Overview

Presentation	Network appliances enabling remote and local access control for your NetShelter SX enclosures.
Lead time	Usually in Stock

General

Provided Equipment	Cable ties Door sensor Installation guide Lock handles Proximity Card Proximity reader Rack Mounting brackets User Manual
External Sensor Connection Type	Alarm Beacon 1 Modbus Output (RS-485) 1 Relay Output 1
APC Universal Sensors Supported	Door contact Dry Contact Humidity Smoke Fluid Spot Leak Temperature Vibration
Product Compatibility	Rack Sensor Pod 150
Number of Universal Sensor Ports	6
Number of Sensor Pods Supported	6
Sensor Temperature Range	15...50 °C +/- 1 °C 32...122 °F +/- 1.8 °F

Physical

Depth	2.32 in (5.9 cm)
Height	1.73 in (4.4 cm)
Product Weight	2.80 lb(US) (1.27 kg)
Number of rack unit	1U
Width	17.01 in (43.2 cm)

Environmental

Ambient Air Temperature for Operation	32...113 °F (0...45 °C)
Operating altitude	0...10000 ft
Relative Humidity	0...95 %
Ambient Air Temperature for Storage	5...149 °F (-15...65 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)
Storage Relative Humidity	0...95 %

Communications & Management

Communication port protocol	A-Link SNMP
-----------------------------	----------------

Ordering and shipping details

GTIN	03606481978011
Package weight(Lbs)	5.40 lb(US) (2.45 kg)

Packing Units

Package 1 Height	7.63 in (19.37 cm)
Package 1 width	35.59 in (90.4 cm)
Package 1 Length	20.83 in (52.9 cm)

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
-------------------	--
