



## 1550 Medium Case Standard

- **Watertight, crushproof, and dustproof**
- Easy open Double Throw latches
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve - balances interior pressure, keeps water out
- Comfortable rubber over-molded handle
- Stainless steel hardware and padlock protectors
- 2 level Pick N Pluck™ with convoluted lid foam
- [Personalized nameplate service available](#)
- [Lifetime Guarantee of Excellence](#)

### CONFIGURATIONS

- 1550** - Standard
- 1554** - With With Padded Dividers
- 1550NF** - With No Foam


### DIMENSIONS

- Interior (L x W x D):** 18.63 x 14.18" x 7.72 (47.3 x 36 x 19.6 cm)
- Exterior (L x W x D):** 20.66 x 17.20" x 8.40 (52.5 x 43.7 x 21.3 cm)
- Lid Depth:** 1.75"
- Bottom Depth:** 5.87"
- Total Depth:** 7.62"
- Int Volume:** 1.18 ft<sup>3</sup>


### MATERIALS

- Body:** Polypropylene
- Latch:** ABS
- O-Ring:** Polymer
- Pins:** Stainless Steel
- Foam:** 1.3 lb Polyurethane
- Purge Body:** ABS
- Purge Vent:** 3 Micron Hydrophobic Non-Woven
- Purge O-Ring:** 70 Shore Nitrile

### COLORS



Black




Silver



Orange



Yellow



OD Green



Desert Tan

## WEIGHT

**Weight With Foam:** 11.90 lbs

**Weight Without Foam:** 10.58 lbs

**Buoyancy:** 69.89 lbs

**Master Pack Weight:** 28.35 lbs

## TEMPERATURE

**Minimum Temperature:** -40°

**Maximum Temperature:** 210°

## APPROVALS

IP67

MIL C-4150J

Def Stan 81-41

STANAG 4280

ATA 300

## FOAM PROPERTIES

**Layer 1 (Lid):** 1.75" Convolute

**Layer 2 (Base):** 0.75" Pad

**Layer 3 (Base):** 2.50" Pick N Pluck

**Layer 4 (Base):** 2.50" Pick N Pluck

## OTHER

**Master Pack:** 2

**Nameplate:** yes

**Military:** yes

### Pelican Products, Inc.

23215 Early Ave • Torrance, CA90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)