

Loom & Tubing Accessories (Clamps, Clips)

Available
in Black and
Natural



Nylon Cable Clamps



Black Nylon Cable Clamps (Package Types)



Natural Nylon Cable Clamps (Package Types)



Nylon Push Mount Cable Clamps

Nylon Cable Clamps

Techspan's 6/6 Nylon Cable Clamps are non-conductive and resist corrosion, salt, gasoline, oil, grease and common solvents. These clamps come in black or natural and have a maximum temperature rating of 85°C (185°F).

Width: 3/8" (9.5mm); Colour: Black

ID Size	Actual Mounting Hole Diameter	10 PCS/PK	100 PCS/PK
3/16" (4.3mm)	#10 .205" (5.2mm)		767500C
1/4" (6.3mm)	#8 .189" (4.8mm)	667076	767076C
5/16" (7.6mm)	#8 .189" (4.8mm)	667053	767053C
3/8" (8.7mm)	#8 .189" (4.8mm)	667054	767054C

Width: 3/8" (9.5mm); Colour: Natural

ID Size	Actual Mounting Hole Diameter	10 PCS/PK	100 PCS/PK
3/16" (4.3mm)	#10 .205" (5.2mm)		766500C
1/4" (6.3mm)	#8 .189" (4.8mm)	666076	766076C
5/16" (7.6mm)	#8 .189" (4.8mm)	666053	766053C
3/8" (8.7mm)	#8 .189" (4.8mm)	666054	766054C

Width: 1/2" (12.5mm); Colour: Black

ID Size	Actual Mounting Hole Diameter	10 PCS/PK	100 PCS/PK
1/8" (3.2mm)	#10 .205" (5.2mm)		767046C
1/2" (12.6mm)	#8 .189" (4.8mm)	*667047	767047C *NEW
5/8" (15.8mm)	#8 .189" (4.8mm)	667077	767077C
3/4" (19.4mm)	#8 .189" (4.8mm)	667078	767078C
1" (25.4mm)	#8 .189" (4.8mm)		767079C
1-1/8" (28.6mm)	#8 .189" (4.8mm)		767049C
1-1/4" (31.8mm)	#8 .189" (4.8mm)		767050C
1-1/2" (36.7mm)	#8 .189" (4.8mm)		767503C

Width: 1/2" (12.5mm); Colour: Natural

ID Size	Actual Mounting Hole Diameter	10 PCS/PK	100 PCS/PK
1/8" (3.2mm)	#10 .205" (5.2mm)		766046C
3/8" (9.5mm)	#8 .189" (4.8mm)		766502C
1/2" (12.6mm)	#8 .189" (4.8mm)	*666047	766047C *NEW
5/8" (15.8mm)	#8 .189" (4.8mm)	666077	766077C
3/4" (19.4mm)	#8 .189" (4.8mm)	666078	766078C
1" (25.4mm)	#8 .189" (4.8mm)		766079C
1-1/8" (28.6mm)	#8 .189" (4.8mm)		766049C
1-1/4" (31.8mm)	#8 .189" (4.8mm)		766050C
1-1/2" (36.7mm)	#8 .189" (4.8mm)		766503C

Nylon Push Mount Cable Clamps

Quick and efficient installation. Base clip mounts in a .25" (6.4 mm) hole. Suitable for chassis and panels .020" to .090" (.50 mm to 2.3 mm) thick.

ID Size	25 PCS/PK
1/4" (6.4mm)	766080
3/8" (9.5mm)	766081
1/2" (12.7mm)	766082