



Main

| | |
|------------------------------|--|
| Range | TeSys |
| Product or component type | Mechanical latch block |
| Product compatibility | LC1DT60A...DT80A TeSys D control relays LC1D09...D38 LC1D40A...D65A LC1DT20...DT40 |
| [Uc] control circuit voltage | 110/127 V AC 50/60 Hz 110/127 V DC |

Complementary

| | |
|-------------------------------|-----------------------|
| Mounting location | Front side |
| Tripping control | Manual Electrical |
| [Ui] rated insulation voltage | 690 V IEC 60947-5-1 |
| Power required in VA | 25 AC |
| Power required in W | 30 W DC |
| Mechanical durability | 500000 cycles |
| Maximum operating rate | 1200 cyc/h |
| On-load factor | 10 % |
| Net Weight | 0.15 lb(US) (0.07 kg) |

Environment

| | |
|---------------------------------------|----------------------------|
| Product certifications | UL CSA |
| IP degree of protection | IP2xVDE 0106 |
| Protective treatment | THIEC 60068 |
| Ambient air temperature for operation | -13...131 °F (-25...55 °C) |
| Ambient air temperature for storage | -40...176 °F (-40...80 °C) |

Ordering and shipping details

| | |
|-----------------------|---------------------------------|
| Category | 22341 - CONTACTOR,D,K,&F ACCESS |
| Discount Schedule | I12 |
| GTIN | 00785901842385 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 0.22 lb(US) (0.10 kg) |
| Returnability | Yes |
| Country of origin | FR |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

| | |
|------------------------------|------------------------|
| Unit Type of Package 1 | PCE |
| Package 1 Height | 1.89 in (4.8 cm) |
| Package 1 width | 2.09 in (5.3 cm) |
| Package 1 Length | 2.60 in (6.6 cm) |
| Unit Type of Package 2 | S01 |
| Number of Units in Package 2 | 32 |
| Package 2 Weight | 7.43 lb(US) (3.369 kg) |
| Package 2 Height | 5.91 in (15 cm) |
| Package 2 width | 5.91 in (15 cm) |
| Package 2 Length | 15.75 in (40 cm) |

Offer Sustainability

| | |
|----------------------------|--|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|