



Product Family
Miller TurboLite Personal Fall Limiters

Never need a shock-absorbing lanyard AGAIN with the 6-ft or 9-ft lightweight personal fall limiters rated for a 400-lb worker!

[Visit MillerFallProtection.com](http://MillerFallProtection.com) >
[Interactive Miller Catalog](#) >
[Access the Miller Photo Gallery](#) >



Product Numbers & Ordering Information

Product Numbers	Details
MFL-1/6FT	6-ft TurboLite Unit Connector: Steel Twist-Lock Carabiner; Lanyard End Connector: Locking Snap Hook
MFL-10/6FT	6-ft TurboLite Unit Connector: Locking Snap Hook; Lanyard End Connector: Locking Rebar Hook
MFL-10-Z7/6FT	6-ft TurboLite; 3,600 lb. Gate Unit Connector: Locking Snap Hook; Lanyard End Connector: Locking Rebar Hook
MFL-11/6FT	6-ft TurboLite Unit Connector: Aluminum Twist-Lock Carabiner; Lanyard End Connector: Aluminum Locking Snap Hook
MFL-12/6FT	6-ft TurboLite Unit Connector: Aluminum Twist-Lock Carabiner; Lanyard End Connector: Aluminum Locking Rebar Hook
MFL-1-Z7/6FT	6-ft TurboLite; 3,600 lb. Gate Unit Connector: Steel Twist-Lock Carabiner; Lanyard End Connector: Locking Snap Hook

Miller TurboLite PFLs



MFL-2/6FT

6-ft TurboLite

Unit Connector: Steel Twist-Lock Carabiner; Lanyard End Connector: Locking Rebar Hook



MFL-2-Z7/6FT

6-ft TurboLite; 3,600 lb. Gate

Unit Connector: Steel Twist-Lock Carabiner; Lanyard End Connector: Locking Rebar Hook



MFL-3/6FT

6-ft TurboLite

Unit Connector: None; Lanyard End Connector: Locking Snap Hook



MFL-3-Z7/6FT

6-ft TurboLite; 3,600 lb. Gate

Unit Connector: None; Lanyard End Connector: Locking Snap Hook



MFL-4/6FT

6-ft TurboLite

Unit Connector: None; Lanyard End Connector: Locking Rebar Hook



MFL-4-Z7/6FT

6-ft TurboLite; 3,600 lb. Gate

Unit Connector: None; Lanyard End Connector: Locking Rebar Hhook



MFL-5/6FT

6-ft TurboLite

Unit Connector: None; Lanyard End Connector: Locking Swivel Snap Hook



MFL-5-Z7/6FT

6-ft TurboLite; 3,600 lb. Gate

Unit Connector: None; Lanyard End Connector: Locking Swivel Snap Hook



MFL-6/6FT

6-ft TurboLite

Unit Connector: None; Lanyard End Connector: Locking Swivel Rebar Hook



MFL-7/6FT

6-ft TurboLite

Unit Connector: D-Ring Swivel Hook; Lanyard End Connector: Locking Snap Hook



MFL-8/6FT

6-ft TurboLite

Unit Connector: D-Ring Swivel Hook; Lanyard End Connector: Locking Rebar Hook



MFL-9/6FT

6-ft TurboLite

Unit Connector: Locking Snap Hook; Lanyard End Connector: Locking Snap Hook
















MFL-9-Z7/6FT













6-ft TurboLite; 3,600 lb. Gate

Unit Connector: Locking Snap Hook; Lanyard End Connector: Locking Snap Hook

Miller TurboLite PFLs

	MFL-11-Z7/6FT	6-ft TurboLite; 3,600 lb. Gate Unit Connector: Aluminum Carabiner; Lanyard End Connector: Aluminum Snap Hook
	MFL-12-Z7/6FT	6-ft TurboLite; 3,600 lb. Gate Unit Connector: Aluminum Carabiner; Lanyard End Connector: Aluminum Rebar Hook
	MFL-14-Z7/6FT	6-ft TurboLite; 3,600 lb. Gate Unit Connector: Aluminum Snap Hook; Lanyard End Connector: Aluminum Snap Hook
	MFL-16-Z7/6FT	6-ft TurboLite; 3,600 lb. Gate No unit connector; Lanyard End Connector: Aluminum Snap Hook
	MFL-17-Z7/6FT	6-ft TurboLite; 3,600 lb. Gate No unit connector; Lanyard End Connector: Aluminum Rebar Hook
	MFL-1/9FT	9-ft TurboLite Unit Connector: Steel Carabiner; Lanyard End Connector: Steel Snap Hook
	MFL-1-Z7/9FT	9-ft TurboLite; 3,600 lb. Gate Unit Connector: Steel Carabiner; Lanyard End Connector: Steel Snap Hook
	MFL-2/9FT	9-ft TurboLite Unit Connector: Steel Carabiner; Lanyard End Connector: Steel Rebar Hook
	MFL-3/9FT	9-ft TurboLite No Connector; Lanyard End Connector: Steel Snap Hook
	MFL-3-Z7/9FT	9-ft TurboLite; 3,600 lb. Gate No Connector; Lanyard End Connector: Steel Snap Hook
	MFL-4/9FT	9-ft TurboLite No Connector; Lanyard End Connector: Steel Rebar Hook
	MFL-5/9FT	9-ft TurboLite No Connector; Lanyard End Connector: Steel Swivel Snap Hook
	MFL-5-Z7/9FT	9-ft TurboLite; 3,600 lb. Gate No Connector; Lanyard End Connector: Steel Swivel Snap Hook

Miller TurboLite PFLs

	MFL-6/9FT	9-ft TurboLite No Connector; Lanyard End Connector: Steel Swivel Rebar Hook
	MFL-9/9FT	9-ft TurboLite Unit Connector: Steel Snap Hook; Lanyard End Connector: Steel Snap Hook
	MFL-9-Z7/9FT	9-ft TurboLite; 3,600 lb. Gate Unit Connector: Steel Snap Hook; Lanyard End Connector: Steel Snap Hook
	MFL-10/9FT	9-ft TurboLite Unit Connector: Steel Snap Hook; Lanyard End Connector: Steel Rebar Hook
	MFL-11/9FT	9-ft TurboLite Unit Connector: Aluminum Carabiner; Lanyard End Connector: Aluminum Snap Hook
	MFL-11-Z7/9FT	9-ft TurboLite; 3,600 lb. Gate Unit Connector: Aluminum Carabiner; Lanyard End Connector: Aluminum Snap Hook
	MFL-12/9FT	9-ft TurboLite Unit Connector: Aluminum Carabiner; Lanyard End Connector: Aluminum Rebar Hook
	MFL-12-Z7/9FT	9-ft TurboLite; 3,600 lb. Gate Unit Connector: Aluminum Carabiner; Lanyard End Connector: Aluminum Rebar Hook
	MFL-14-Z7/9FT	9-ft TurboLite; 3,600 lb. Gate Unit Connector: Aluminum Snap Hook; Lanyard End Connector: Aluminum Snap Hook
	MFL-15-Z7/9FT	9-ft TurboLite; 3,600 lb. Gate Unit Connector: Aluminum Snap Hook; Lanyard End Connector: Aluminum Rebar Hook
	MFL-16-Z7/9FT	9-ft TurboLite; 3,600 lb. Gate No Unit Connector; Lanyard End Connector: Aluminum Snap Hook
	MFL-17-Z7/9FT	9-ft TurboLite; 3,600 lb. Gate No Unit Connector; Lanyard End Connector: Aluminum Rebar Hook

Overview

Key Features

Cost-effective, compact and lightweight, Miller TurboLite Personal Fall Limiters make the need for shock-absorbing

lanyards obsolete.

- Reduces fall clearance requirements
- Available in 6-ft and 9-ft lengths to meet the needs of a wide variety of applications
- Extremely compact and lightweight, comparable to a shock-absorbing lanyard
- Attaches directly to the back D-ring of a harness for increased mobility
- High-impact nylon housing and abrasion-resistant webbing provide long service life
- Integral swivel prevents lifeline from twisting
- Rated for up to a 400 lb. (181.4 kg) worker
- Twin models available for 100% tie-off
- ANSI Z359.14, ANSI A10.32 and CSA compliant models available (All models meet OSHA requirements)

Miller 6-foot TurboLite PFL

- Ideal replacement for a 6-ft. shock-absorbing lanyard
- Models start at just 1.9 lbs. (0.86 kg)

Miller 9-foot TurboLite PFL

- Provides 9-ft. of working length, an ideal solution for scaffolding and order picker applications
- Lightest 9-ft. unit on the market - Models start at just 2.3 lbs. (1.0 kg)

Recommended Industries/Use

- Construction
- Oil and Gas

Hazards

- Confined Space
- Fall from height

Regulations

- - Meets all applicable OSHA, ANSI and CSA standards

Warranty Information

We sincerely believe that our fall protection equipment is the best in the world. Our products endure rigorous test to ensure that the fall protection equipment you trust is manufactured to the highest standards. Miller fall protection products are tested to withstand normal wear and tear, but are not indestructible and can be damaged by misuse. Our Limited Lifetime Warranty does not apply to normal wear and tear or abusive treatment of the product. In the unlikely event that you should discover defects in either workmanship or materials, under our Limited Lifetime Warranty, we will repair or replace the product at our expense. If a replacement is necessary and your product is no longer available, a comparable product will be substituted. Should a product issue surface, contact us at 800/873-5242. Manufacturing specifications are subject to change without notice.

Literature & Documents

TurboLite-TwinTurbo-brochure - US

http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Fall_Protection/Fall_Limiters/Self-Retracting_Lifelines/4294976298/1033.aspx

View Miller TurboLite/Twin Turbo Family Brochure

SP408 TurboLite Series Spec Sheet - US

http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Fall_Protection/Fall_Limiters/Self-Retracting_Lifelines/16181/1033.aspx

SP408 6-ft Miller TurboLite Series Spec Sheet

SP482 9-ft TurboLite spec - US

http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Fall_Protection/Fall_Limiters/Self-Retracting_Lifelines/4294976315/1033.aspx

SP482 9-ft Miller TurboLite Series Spec Sheet

Training & Proper Use

Miller TurboLite PFLs

Proper product training and professional fall protection training is recommended. Refer to Product Use Instructions enclosed with products.

Additional Information

800/873-5242 or email: hsptechsupport@honeywell.com

Technical Support

Contact Honeywell Technical Service at 800/873-5242 or email: hsptechsupport@honeywell.com

RELATED PRODUCTS

© Honeywell International Inc.