

**H16,0/12****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



For conductors from 10.0 to 185.0 mm<sup>2</sup> (AWG 7 - 350 MCM)

tin-plated copper

dimensional tolerances to DIN 46228 part 1

- supplied loose in poly-bag

**General ordering data**

Type	H16,0/12
Order No.	<a href="#">0492500000</a>
Version	Wire end ferrule, 16 mm <sup>2</sup>
GTIN (EAN)	4008190114190
Qty.	500 pc(s).

**Data sheet**

**H16,0/12**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data**

**Dimensions and weights**

Length	12 mm	Net weight	0.35 g
--------	-------	------------	--------

**Product data**

Conductor cross-section	16 mm <sup>2</sup>	Wire connection cross section AWG, max.	AWG 6
Contact surface diameter (D1)	5.8 mm	Collar diameter (D2)	7.5 mm

**Classifications**

ETIM 3.0	EC000005	ETIM 4.0	EC000005
ETIM 5.0	EC000005	ETIM 6.0	EC000005
UNSPSC	31-16-31-02	eClass 5.1	27-40-02-01
eClass 6.2	27-40-02-01	eClass 7.1	27-40-02-01
eClass 8.1	27-40-02-01	eClass 9.0	27400201

**Approvals**

Approvals



ROHS Conform