



### Overview

Lead time	Usually in Stock
-----------	------------------

### General

Provided Equipment	Installation guide
--------------------	--------------------

### Physical

Depth	27.56 in (70 cm)
Height	6.26 in (15.9 cm)
Product Weight	221.45 lb(US) (100.45 kg)
Width	16.85 in (42.8 cm)

### Conformance

Product Certifications	CE Eurobat General Purpose
Standards	UL 1778

### Environmental

Ambient Air Temperature for Operation	64...81 °F (18...27 °C)
Operating altitude	0...3333 ft
Relative Humidity	0...95 %
Ambient Air Temperature for Storage	5...104 °F (-15...40 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)
Storage Relative Humidity	0...95 %

### Batteries & Runtime

Battery Placement	Internal Battery
Battery blocks per string	4
Battery Slots Empty	0
Included Battery Modules	0
Battery Voltage	384 V
Battery Type	VRLA
Battery power in VAh	3456 VAh



### Ordering and shipping details

Package weight(Lbs)	236.78 lb(US) (107.4 kg)
---------------------	--------------------------

## Packing Units

Package 1 Height	7.09 in (18 cm)
Package 1 width	23.62 in (60 cm)
Package 1 Length	31.89 in (81 cm)
Number of Units in Package 3	7

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Take-back	Take-back program available