



## Main

Product or component type	Single Throw Safety Switch
Series name	General duty

## Complementary

Device composition	Neutral (factory installed)
Disconnecter device type	Fusible disconnect
Short-circuit current	100 kA maximum cartridge
Device mounting	Surface
Number of poles	2
Electrical connection	Lugs
[Ue] rated operational voltage	120/240 V AC
AWG gauge	AWG 1/0...750 kcmil copper or aluminium
Maximum Width	22.25 in (565.15 mm)
Height	30.63 in (778.00 mm)
Depth	10.13 in (257.30 mm)
Tightening torque	340 lbf.in (38.41 N.m) AWG 1/0...250 kcmil

## Environment

Product certifications	CSA
NEMA degree of protection	NEMA 3R galvanized steel

## Ordering and shipping details

Category	00008-H&HU, 2&3P, N1, 30-200A
Discount Schedule	DE1
GTIN	00785901204756
Package weight(Lbs)	66.00 lb(US) (29.937 kg)
Returnability	Yes
Country of origin	MX

## Packing Units

Package 1 Height	1.00 ft (0.305 m)
Package 1 width	2.17 ft (0.660 m)
Package 1 Length	3.83 ft (1.168 m)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

## Contractual warranty

Warranty	18 months
----------	-----------