

Product Datasheet

Characteristic

9070T5000D31

TRFMR CONTROL 5000VA 240/480V- 120/240V



Main

product or component type	Industrial Control Transformer
rated power in VA	5000 VA
primary voltage	240 x 480 V 230 x 460 V 220 x 440 V
secondary voltage	120/240 V 115/230 V 110/220 V
range of product	T

Complementary

Phase	1 phase
rated power in VA	5000 VA per UL 5000 VA per CSA 5000 VA per NOM 3000 VA per CE
primary voltage	220 x 440 V : 110/220 V 230 x 460 V : 115/230 V 240 x 480 V : 120/240 V
temperature rise	115 °C
electrical connection	screw clamp terminals
height	8.75 in
width	9 in
depth	9.15 in
material	copper winding
product compatibility	FSC2

Environment

product certifications	CE UL listed file E61239 CSA file LR37055 guide 184-N-90
NEMA degree of protection	not rated (open device)
insulation temperature	356 °F (180 °C)

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1227 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations