

CD225NR

400A, 2 POLE, FUSIBLE, TYPE 3R, GDSS

Main

Action	Single Throw
Ampere Rating	400A
Approvals	CSA Certified
Depth	10.13 Inches
Disconnect Type	Fusible Disconnect
Electrical Interlock	No
Enclosure Rating	NEMA 3R
Factory Installed Neutral	Yes
Height	30.63 Inches
Hub Type	H
Marketing Trade Name	Square D
Material	Galvannealed Steel
Maximum Voltage Rating	120/240VAC
Mounting Type	Surface Mount
Number of Poles	2-Pole
Short Circuit Current Rating	100000 AIR
Type	Fusible General Duty
Width	21.38 Inches
Wire Size	(1) 1/0-600 MCM (AL), (1) 1/0-600 MCM (CU)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.