

**Dekafix
DEK 5 GW 6**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



{Reference (Object) not found: prod32188580854228}

General ordering data

Type	DEK 5 GW 6
Order No.	0522660006
Version	Dekafix, Card, 5 x 5 mm, Pitch in mm (P): 5.00 White
GTIN (EAN)	4008190160890
Qty.	500 pc(s).

Data sheet

**Dekafix
DEK 5 GW 6**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

Length	5 mm	Width	5 mm
Net weight	0.04 g		

General data

Colour	White	Colour of printing	Black
Length	5 mm	Material	Polyamide 66
Material colour according to resistance code	9	Operating temperature range, max.	100 °C
Operating temperature range, min.	-40 °C	Orientation of print	horizontal
Printed characters	Numbers	Printing method	MC Laser
UL 94 flammability rating	V-2	Width	5 mm

Connector markers

Pitch in mm (P)	5 mm
-----------------	------

Classifications

ETIM 3.0	EC000761	ETIM 4.0	EC000761
ETIM 5.0	EC000761	ETIM 6.0	EC000761
UNSPSC	30-21-18-07	eClass 5.1	27-14-11-37
eClass 6.2	27-14-11-37	eClass 7.1	27-14-11-37

Approvals

Approvals



ROHS Conform