



Universal Applications

Toggle Switches

Medium-Duty Toggle Switches



Rating: 20A @ 12VDC. CSA Approved. Universal applications (fits panels up to 9/32").



765047 765042 765046 765041

S.P.S.T. (SINGLE POLE – SINGLE THROW)

Positions	Circuitry	Terminal Type	Handle Length/Type	1 PC/PK	25 PCS/PK
2	ON-OFF	2 Blades	Std. 11/16" Chrome	765047	765047B
2	ON-OFF	2 Blades	Long 1-1/2" Chrome	765042	765042B
2	ON-OFF	2 Screws	Std. 11/16" Chrome	765046	765046B
2	ON-OFF	2 Screws	Long 1-1/2" Chrome	765041	765041B



765052 765055 765054 765056

S.P.D.T. (SINGLE POLE – DOUBLE THROW)

Positions	Circuitry	Terminal Type	Handle Length/Type	1 PC/PK	25 PCS/PK
2	ON-ON	3 Blades	Std. 11/16" Chrome	765052	765052B
3	ON-OFF-ON	3 Blades	Std. 11/16" Chrome	765056	765056B
2	ON-ON	3 Screws	Std. 11/16" Chrome	765054	765054B
3	ON-OFF-ON	3 Screws	Std. 11/16" Chrome	765055	765055B



765059 765058

D.P.S.T. (DOUBLE POLE – SINGLE THROW)

Positions	Circuitry	Terminal Type	Handle Length/Type	1 PC/PK	25 PCS/PK
2	ON-OFF	4 Blades	Std. 11/16" Chrome	765059	765059B
2	ON-OFF	4 Screws	Std. 11/16" Chrome	765058	765058B



765063 765066 765064 765065

D.P.D.T. (DOUBLE POLE – DOUBLE THROW)

Positions	Circuitry	Terminal Type	Handle Length/Type	1 PC/PK	25 PCS/PK
2	ON-ON	6 Blades	Std. 11/16" Chrome	765063	765063B
3	ON-OFF-ON	6 Blades	Std. 11/16" Chrome	765066	765066B
2	ON-ON	6 Screws	Std. 11/16" Chrome	765064	765064B
3	ON-OFF-ON	6 Screws	Std. 11/16" Chrome	765065	765065B



765043 765049 765048†

Medium-Duty 'Momentary' Toggle Switches



Rating: 20A @ 12VDC. CSA Approved. Universal applications (fits panels up to 9/32").

S.P.S.T. (SINGLE POLE – SINGLE THROW)

Positions	Circuitry	Terminal Type	Handle Length/Type	1 PC/PK	25 PCS/PK
2	Mom ON-OFF	2 Blades	Std. 11/16" Chrome	765043	765043B
2	Mom ON-OFF	2 Screws	Std. 11/16" Chrome	765049	765049B
2	ON-Mom OFF	2 Screws	Long 1-1/2" Chrome	765048†	

†765048 is not CSA approved



765062 765057 765071

S.P.D.T. (SINGLE POLE – DOUBLE THROW)

Positions	Circuitry	Terminal Type	Handle Length/Type	1 PC/PK	25 PCS/PK
3	Mom ON-OFF-Mom ON	3 Blades	Std. 11/16" Chrome	765062	765062B
3	Mom ON-OFF-Mom ON	3 Screws	Std. 11/16" Chrome	765057	765057B
3	ON-OFF-Mom ON	3 Screws	Std. 11/16" Chrome	765071	765071B



765074 765069 765070 765067

D.P.D.T. (DOUBLE POLE – DOUBLE THROW)

Positions	Circuitry	Terminal Type	Handle Length/Type	1 PC/PK	25 PCS/PK
3	Mom ON-OFF-ON	6 Blades	Std. 11/16" Chrome	765074	765074B
3	Mom ON-OFF-ON	6 Screws	Std. 11/16" Chrome	765069	765069B
3	Mom ON-OFF-Mom ON	6 Blades	Std. 11/16" Chrome	765070	765070B
3	Mom ON-OFF-Mom ON	6 Screws	Std. 11/16" Chrome	765067	765067B

Toggle Switches & Accessories

Medium-Duty Toggle Switch (Weather-Resistant) *NEW

SPST with Standard 11/16" 'Bat' Handle. Mounting stem: 15/32". Rating 20A @ 12VDC

Type	1 PC/PK	25 PCS/PK
2 Position (ON-OFF)	*765010	*765010B *NEW

Feature	Benefit
O-Ring Seal + Plastic Coating	Weatherproofs the switch
On/Off Face Plate	Easily identifies the current function of switch
Wire Leads – Tin Plated Copper (14GA, 8" Long)	Tin Plating on the copper prolongs life of switch



*765010

Toggle Switch Accessories

Toggle Switch Flip Cover Guard[†]

- Spring loaded snap action holds this Cover Guard in the Up or Down position Switch cannot be operated with the cover in the down position
- Can easily be added to an already installed toggle switch by unscrewing and replacing the face-nut • Faceplate is steel with black glossy finish
- Recommended for use with Toggle Switches with:
 - A standard 15/32" mounting stem
 - On-Off or On-On Functions
 - An 11/16" standard 'Bat' handle
 - A Keyway in the bushing

Description	1 PC/PK	25 PCS/PK
Toggle Switch Flip Cover Guard	*765004	*765004B *NEW



*765004

[†] Toggle switch is not included (for illustrative purposes only)

Toggle Switch Boot Seals

Made from silicone rubber that is bonded to a standard 15/32" – 32 thread nickel plated brass hex-nut. The rubber actually forms an O-Ring when the nut is tightened onto the stem of a toggle switch. Boot seals help protect toggle switches from dirt, moisture and salt spray.

Full-Boot Seals (Closed)

Covers Toggle Switches with a 15/32" diameter mounting stem and an 11/16" 'Bat' Handle

Colour	1 PC/PK	25 PCS/PK
Black	765001	765001B
Grey	*765005	*765005B *NEW
Red	*765006	*765006B *NEW



765001

*765005

*765006

Full-Boot Seals (Closed)

Half-Boot Seals (Open)

Covers all Toggle Switches that have a 15/32" diameter mounting stem. Not to be used with Toggle Switches with square-ended handles.

Colour	1 PC/PK	25 PCS/PK
Black	765003	765003B
Grey	*765011	*765011B *NEW



765003

*765011

Half-Boot Seals (Open)

Toggle Switch Face Plate

Type	1 PC/PK	25 PCS/PK
On-Off	765000	765000B



765000

Toggle Switch Face Plate

Toggle Switches



765101



765103



765102



*765109



*765108



765105



765117



765120



765075



765072



765073



Medium-Duty Toggle Switches (Nylon Handle)

Decorator style toggle switches with an O-ring seal between toggle and bushing for splash proof reliability. Lighted versions have a transparent Lexan handle (20A @ 12VDC). Non-lighted versions have solid black handles and are rated at 35A @ 12VDC. CSA Approved where shown. Universal applications (fits panels up to 9/32")

S.P.S.T. (SINGLE POLE – SINGLE THROW)

Positions	Circuitry	Terminal Type	Amp Rating	Handle Length/Type	1 PC/PK
2	ON-OFF	2 Blades	35A @ 12VDC	Std 11/16" Black	765101
2	ON-OFF	4 Blades	20A @ 12VDC	Std 11/16" Lighted	765103
2	ON-OFF	4 Screws	20A @ 12VDC	Std 11/16" Lighted	765102

D.P.S.T (DOUBLE THROW – SINGLE POLE)

Positions	Circuitry	Terminal Type	Amp Rating	Handle Length/Type	1 PC/PK
2	ON-OFF	4 Blades	35A @ 12VDC	Std 11/16" Black	*765109 *NEW
2	ON-OFF	4 Screws	35A @ 12VDC	Std 11/16" Black	*765108 *NEW

Medium-Duty 'Momentary' Toggle Switches (Nylon Handle)

Decorator style toggle switches with an O-ring seal between toggle and bushing for splash proof reliability. Solid black nylon handles. Rating: 35A @ 12VDC. CSA Approved where shown. Universal applications (fits panels up to 9/32")

S.P.D.T (SINGLE POLE – DOUBLE THROW)

Positions	Circuitry	Terminal Type	Amp Rating	Handle Length/Type	1 PC/PK
3	Mom ON-OFF- Mom ON	3 Blades	35A @ 12VDC	Std 11/16" Black	765105

D.P.D.T (DOUBLE POLE – DOUBLE THROW)

Positions	Circuitry	Terminal Type	Amp Rating	Handle Length/Type	1 PC/PK
3	Mom ON-OFF- Mom ON	6 Blades	35A @ 12VDC	Std 11/16" Black	765117

Medium-Duty Toggle Switches (Nylon, Paddle Handle)

S.P.S.T. (SINGLE POLE – SINGLE THROW)

Positions	Circuitry	Terminal Type	Amp Rating	Handle Length/Type	1 PC/PK
2	ON-OFF	2 Blades	20A @ 12VDC	Std 1" Black	765120

Light-Duty Toggle Switches

The best combination of space-saving size and economy for universal light-duty applications. CSA approved where shown.

S.P.S.T. (SINGLE POLE – SINGLE THROW)

Positions	Circuitry	Terminal Type	ON – OFF Faceplate	Description	1 PC/PK	25 PCS/PK
2	ON-OFF	2 Blades	No	35A @ 6V, 20A @ 12V. Mounting stem: 7/16" diameter, 3/8" long.	765075	765075B
2	ON-OFF	2 Blades	Yes	6A @ 125V, 3A @ 250V. Mounting stem: 15/32" diameter, 15/32" long.	765072	765072B
2	ON-OFF	2 Blades	Yes	6A @ 125V, 3A @ 250V. Mounting stem: 15/32" diameter, 15/32" long. 2 x 6" wire leads	765073	765073B

Toggle Switches & Rocker Switches

Heavy-Duty Toggle Switches

Oversized internal copper contacts will carry up to 50 amp current loads. Provides a long service life. (Note: Bladed terminals will carry 30 amps)

S.P.S.T (SINGLE POLE – SINGLE THROW)

Positions	Circuitry	Terminal Type	Amp Rating	Handle Length/Type	1 PC/PK
2	ON-OFF	2 Blades	30A @ 12VDC	Std. 1" Chrome	765033
2	ON-OFF	2 Screws	50A @ 12VDC	Std. 1" Chrome	765030
2	ON-OFF	2 Screws	50A @ 12VDC	Std. 1" Black	765012
2	ON-OFF	2 Screws	50A @ 12VDC	Long 1-1/2" Chrome	765031



S.P.D.T (SINGLE POLE – DOUBLE THROW)

Positions	Circuitry	Terminal Type	Amp Rating	Handle Length/Type	1 PC/PK
3	ON-OFF-ON	3 Screws	50A @ 12VDC	Std 1" Chrome	765034



765034

Heavy-Duty 'Momentary' Toggle Switches

S.P.D.T (SINGLE POLE – DOUBLE THROW)

Positions	Circuitry	Terminal Type	Amp Rating	Handle Length/Type	1 PC/PK
3	Mom ON-OFF-Mom ON	3 Screws	50A @ 12VDC	Std. 1" Chrome	765032
3	Mom ON-OFF-Mom ON	3 Screws	50A @ 12VDC	Long. 1-1/2" Chrome	765020



765032



765020

Rocker Switches (Full Size)

Universal design. 'Snap-in' mounting fits .830" x 1.45" panel cut-out that are .093", .125" or .187" thick. These rocker switches have a nylon bezel actuator and housing. Rating: 20A @ 12VDC. For lighted units, pilot light illuminates when the switch is ON.

S.P.S.T. (SINGLE POLE – SINGLE THROW)

Positions	Circuitry	Terminal Type	Actuator	1 PC/PK
2	ON-OFF	2 Blades	Black (No Light)	765131
2	ON-OFF	2 Screws	Black (No Light)	765130
2	ON-OFF	3 Blades	Black with Red Pilot Light	765135
2	ON-OFF	3 Screws	Black with Red Pilot Light	765134
2	ON-OFF	3 Screws	Black with Amber Pilot Light	765137
2	ON-OFF	3 Screws	Black with Green Pilot Light	765136



765131



765130



765135



765134



765137



765136

Rocker Switches (Round)

Round rocker switches feature an actuator that illuminates when turned to the "On" position. 20A @ 12VDC. Recommended mounting hole diameter: 0.795"



S.P.S.T. (SINGLE POLE – SINGLE THROW)

Positions	Circuitry	Terminal Type	Actuator	1 PC/PK
2	ON-OFF	3 Blade	Amber	*765141 *NEW
2	ON-OFF	3 Blade	Blue	*765143 *NEW
2	ON-OFF	3 Blade	Green	*765142 *NEW
2	ON-OFF	3 Blade	Red	*765140 *NEW



*765141



*765143



*765142



*765140