

## T5 HO Program Start

\* Based on a 3 hour start \*\* Based on a 12 hour start

Order code	Description	Watts (W)	Base	Colour temp. (K)	CRI	Rated life PS/PRS ballast 3-12 hrs	Initial lumens (lm)	Mean lumens (lm)	Nominal length (in.) (mm)		Efficacy (lm/W)	Case qty
59193*	F24T5/35K/8/HO/PS/G5/ELUME	24	Min Bipin	3 500	85	24 000* 30 000**	2 000	1 900	22	559	83	25
59194*	F24T5/41K/8/HO/PS/G5/ELUME	24	Min Bipin	4 100	85	24 000* 30 000**	2 000	1 900	22	559	83	25
59195*	F24T5/50K/8/HO/PS/G5/ELUME	24	Min Bipin	5 000	85	24 000* 30 000**	1 900	1 805	22	559	79	25
59199*	F39T5/35K/8/HO/PS/G5/ELUME	39	Min Bipin	3 500	85	24 000* 30 000**	3 500	3 325	34	864	90	25
59200*	F39T5/41K/8/HO/PS/G5/ELUME	39	Min Bipin	4 100	85	24 000* 30 000**	3 500	3 325	34	864	90	25
59201*	F39T5/50K/8/HO/PS/G5/ELUME	39	Min Bipin	5 000	85	24 000* 30 000**	3 500	3 325	34	864	90	25
58735*	F54T5/35K/8/HO/PS/G5/ELUME	54	Min Bipin	3 500	85	24 000* 30 000**	5 000	4 750	46	1 168	93	25
58734*	F54T5/41K/8/HO/PS/G5/ELUME	54	Min Bipin	4 100	85	24 000* 30 000**	5 000	4 750	46	1 168	93	25
59202*	F54T5/50K/8/HO/PS/G5/ELUME	54	Min Bipin	5 000	85	24 000* 30 000**	4 800	4 550	46	1 168	89	25

### Features

- Higher initial and maintained lumens than conventional T12 lamps
- Better colour rendering
- TCLP compliant
- Available in a variety of colour temperatures

### Applications

- Hotels
- Schools
- Ambient lighting (Living room, kitchen, under cabinet lighting)
- Retail stores
- Hospitals
- Offices



Dia. = 1/2 in. (26 mm)

## T8 Preheat Start

Order code	Description	Watts (W)	Base	Colour temp. (K)	CRI	Average life (hrs)	Initial lumens (lm)	Mean lumens (lm)	Nominal length (in.) (mm)		Efficacy (lm/W)	Case qty
56514	F15T8/CW/PH/G13/ELUME	15	Med Bipin	4 100	62	7 500	610	573	18	457	41	48
56515	F15T8/DL/PH/G13/ELUME	15	Med Bipin	6 500	72	7 500	560	526	18	457	37	48

## T8 800 Series - Rapid Start

\* Based on a 3 hour start \*\* Based on a 12 hour start

Order code	Description	Watts (W)	Base	Colour temp. (K)	CRI	Rated life on IS ballast 3-12 hrs	Rated life PS/PRS ballast 3-12 hrs	Initial lumens (lm)	Mean lumens (lm)	Nominal length (in.) (mm)		Efficacy (lm/W)	Case qty
62513	F32T8/35K/8/RS/G13/ELUME/BULK	32	Med Bipin	3 500	85	24 000* 30 000**	40 000* 42 000**	3 050	2 900	48	1 220	95	25
62514	F32T8/41K/8/RS/G13/ELUME/BULK	32	Med Bipin	4 100	85	24 000* 30 000**	40 000* 42 000**	3 000	2 850	48	1 220	94	25
62515	F32T8/50K/8/RS/G13/ELUME/BULK	32	Med Bipin	5 000	85	24 000* 30 000**	40 000* 42 000**	2 950	2 800	48	1 220	92	25
62516	F32T8/65K/8/RS/G13/ELUME/BULK	32	Med Bipin	6 500	85	24 000* 30 000**	40 000* 42 000**	2 900	2 750	48	1 220	91	25



Dia. = 1 1/2 in. (29.5 mm)

## CIRCLINE Rapid Start

Order code	Description	Watts (W)	Base	Colour temp. (K)	CRI	Average life (hrs)	Initial lumens (lm)	Mean lumens (lm)	Nominal length (in.) (mm)		Efficacy (lm/W)	Case qty
56516	FC8T9/CW/RS/4P/ELUME	22	Circline 4-Pin	4 100	60	12 000	1 150	1 095	9	229	52	24
56517	FC12T9/CW/RS/4P/ELUME	32	Circline 4-Pin	4 100	85	12 000	1 570	1 495	12	305	49	24