

Main

| | |
|------------------------|--|
| Application | Specifically designed to handle high inrush associated with contactors and relays for applications such as conveyor systems, paint lines, punch presses or overhead cranes |
| Approvals | UL Listed File Number: E61239 - CSA Certified File Number: LR37055 Guide: 184-N-90 - CE Marked |
| Depth | 3.59 Inches |
| Enclosure Type | Open |
| Height | 3.20 Inches |
| Insulation Temperature | 130 Degrees C |
| Mounting Type | Panel |
| Phase | 1-Phase |
| Primary | 120x240V |
| Rating | 200VA |
| Secondary | 24V |
| Temperature Rise | 80 Degrees C |
| Terminal Type | Screw Clamp |
| Type | T |
| Width | 3.75 Inches |
| Winding Material | Copper |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.