



Main

| | |
|-----------------------------|---|
| Product or Component Type | Circuit breaker |
| Range | PowerPact P |
| Current Sensor Rating Range | 1200 A |
| Rated Current | 1200 A |
| Breaking Capacity | 65 kA 240 V AC 35 kA at 480 V AC 18 kA 600 V AC |
| Trip Unit Technology | Electronic, basic, ET 1.0I, LI |
| AWG Gauge | AWG 3/0...500 kcmil aluminum/copper)4 |

Complementary

| | |
|-----------------------------|--|
| Certifications | IEC UL listed CSA |
| Rated operational Voltage | 600 V AC |
| Module Type | P-Frame |
| Mounting Location | Busbar |
| Mounting Mode | I-Line |
| Poles Description | 3P |
| Circuit Breaker Rating Code | G |
| Continuous Current Rating | 80 % |
| Electrical Connection | I-Line connection line Lugs load |
| Tightening Torque | 442.54 lbf.in (50 N.m) 0.15...0.37 in ² (95...240 mm ²) AWG 3/0...500 kcmil) 8.85...11.51 lbf.in (1.0...1.3 N.m) |
| Height | 16.16 in (410.46 mm) |
| Width | 8.27 in (210.06 mm) |
| Depth | 8.05 in (204.47 mm) |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Packing Units

| | |
|------------------|--------------------------|
| Package 1 Weight | 35.85 lb(US) (16.261 kg) |
| Package 1 Height | 12.20 in (30.988 cm) |
| Package 1 width | 11.90 in (30.226 cm) |
| Package 1 Length | 20.50 in (52.070 cm) |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End of Life Information |
| PVC free | Yes |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|