



Overview

Presentation	Network appliances enabling remote and local access control for your NetShelter SX enclosures.
Lead time	Usually in Stock

General

Provided Equipment	Cable ties Door sensor Installation guide Lock handles Proximity reader Rack Mounting brackets User Manual
--------------------	--

Physical

Depth	2.32 in (5.9 cm)
Height	1.73 in (4.4 cm)
Product Weight	2.80 lb(US) (1.27 kg)
Number of rack unit	1U
Width	17.01 in (43.2 cm)

Environmental

Ambient Air Temperature for Operation	32...113 °F (0...45 °C)
Operating altitude	0...10000 ft
Relative Humidity	0...95 %
Ambient Air Temperature for Storage	5...149 °F (-15...65 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)
Storage Relative Humidity	0...95 %

Communications & Management

Communication port protocol	A-Link SNMP
-----------------------------	----------------

Ordering and shipping details

GTIN	03606481978028
Package weight(Lbs)	5.40 lb(US) (2.45 kg)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Package 1 Height	7.64 in (19.4 cm)
Package 1 width	35.59 in (90.4 cm)
Package 1 Length	20.83 in (52.9 cm)

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
-------------------	--
