



Main

Product or component type	Motor starter
Type	S
Control Circuit Type	Separate control circuit

Complementary

Control Circuit Voltage	110 V AC 50 Hz 120 V AC 60 Hz
Motor starter type	Non reversing
Current Rating	135 A
Number of Poles	3P
Number of Phases	3 phase
Horsepower Rating	40 HP 200 V AC 50 HP 230 V AC 100 HP 460 V AC 100 HP 575 V AC
Maximum Voltage Rating	600 V AC
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Without
Product compatibility	Circuit-breaker: 10 kA at 600 V AC Fuse: 10 kA at 600 V AC
Thermal overload type	Melting alloy 3
Electrical connection	Screw clamp terminals
NEMA size	4
Height	25.16 in (639 mm)
Depth	9.02 in (229 mm)
Maximum Width	11.26 in (286 mm)

Environment

Enclosure Type	NEMA 1 painted sheet steel
Product certifications	UL Listed CSA NEMA

Ordering and shipping details

Category	21193 - 8502,36 SE,SF(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	00785901832232
Nbr. of units in pkg.	1
Package weight(Lbs)	43.31 lb(US) (19.65 kg)

Returnability	No
Country of origin	MX

Packing Units

Package 1 Height	10.60 in (26.924 cm)
Package 1 width	11.90 in (30.226 cm)
Package 1 Length	25.50 in (64.770 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------