

Product Datasheet

Characteristic

XVUC26

Ø 60 mm illuminated LED unit - steady - blue - IP65 - 24 V AC/DC



Main

range of product	Harmony XVU
product or component type	Modular tower light
beacon or indicator bank unit type	LED unit
mounting diameter	2.36 in (60 mm)
component name	XVU
light source	LED blue
device application	Machine tools Packaging machine Automotive

Complementary

signalling type	Steady
assembly style	Up to 4 units with buzzer Customer assembly, up to 5 units
material	PC (polycarbonate) V-0 flame retardant conforming to UL 94 PC (polycarbonate) V-2 flame retardant conforming to UL 94
[Us] rated supply voltage	24 V AC/DC
power dissipation in W	<= 2.5 W
current consumption	<= 50 mA
signalling type	Steady
length	1.97 in (50 mm)
product weight	0.14 lb(US) (0.064 kg)

Environment

product certifications	CE RoHS CSA UL
ambient air temperature for storage	-40...158 °F (-40...70 °C)
IP degree of protection	IP65
ambient air temperature for operation	-13...122 °F (-25...50 °C)
vibration resistance	2 gn

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1529 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available