

Hole Saws

Hole-Saw Arbors and Accessories

- Cat. No. 31905 is for use with all Klein hole saws.
- Cat. No. 31906 is for use with Klein hole saws 1-3/8" to 6-6/8" (35 mm- 162 mm).
- Fast and easy to engage and disengage hole saws.
- Steel construction for long life.
- 118° split point pilot bits.
- 31905 includes arbor adaptor for 5/8"-18.
- Hardened mandrels for long thread life.



Cat. No.	Shank Style	Pins	Shank Size	Electric Drill Size	Thread Size	Weight (lbs.)
31905	hexagonal	N	3/8" (10 mm)	1/2" and larger	1/2" - 20	.16
31906	hexagonal	Y	7/16" (11 mm)	1/2" and larger	5/8" - 18	.16

Replacement Pilot Drills for Hole-Saw Arbors		Weight (lbs.)
31907	1/4" Replacement Pilot Drill Bit, 1/4" x 3-1/4"	.02

Electrician's Hole Saw Kit

NEW!

- Optimized for cutting steel. Also cuts stainless steel.
- Cuts precise holes in stainless steel and mild steel, drywall, ceiling tile, laminates, wood and plastic.
- Longest lasting, fastest cutting blade on the market.
- Heavy-duty steel construction includes 5 mil back plate to withstand abuse.
- Hex-shaped base for easy removal from arbor.
- Contains the most popular sizes for basic electrical work.
- All components are packed in a rust-proof, molded plastic carrying case.

Cat. No.	Set Contains	Weight (lbs.)
31902		2.60

Hole Saws		Arbors	
Cat. No.	Size	Cat. No.	Size
31914	7/8" (22 mm)	31905	3/8" (10 mm)
31918	1-1/8" (29 mm)	31906	3/8" (10 mm)
31922	1-3/8" (35 mm)		
31928	1-3/4" (44 mm)		
31932	2" (52 mm)		
31940	2-1/2" (64 mm)		



Adjustable Hole Saw

- Quickly and smoothly cuts cleaner holes in drywall and ceiling tiles.
- Blades adjust to cut holes from 2" to 7" in diameter.
- Fits most 3/8" and 1/2" drill chucks.
- No binding while cutting.
- No additional tools needed to adjust the hole saw.
- Dust shield catches ceiling debris (2 included).
- Hex key included.

Cat. No.	Range	Weight (lbs.)
53731	2" - 7" (51 mm - 177 mm)	.31



All dimensions are in inches and (millimeters).



NOTE: Read and follow safety instructions in power tool owner's manual.

www.kleintools.com

See page 296 for additional information on warnings.