



Main

Product or component type	Miniature circuit-breaker
Range of product	QOU
Circuit breaker type	High magnetic
Circuit breaker application	HACR and Switching Duty rated

Complementary

[In] rated current	20 A
Electrical connection	Slotted box lugs, line side Slotted box lugs, load side
[Ue] rated operational voltage	120/240 V AC
Mounting mode	Unit mount
AWG gauge	AWG 14...AWG 2 aluminum/copper
Height	4.05 in (102.87 mm)
Depth	2.95 in (74.93 mm)
Width	0.75 in (19.05 mm)
Tightening torque	45 lbf.in (5.08 N.m) AWG 14...AWG 2)

Environment

Product certifications	CSA UL listed IEC
------------------------	-------------------------

Packing Units

Package 1 Weight	5.92 oz (167.829 g)
Package 1 Height	1.00 in (2.540 cm)
Package 1 width	3.10 in (7.874 cm)

Package 1 Length	4.40 in (11.176 cm)
------------------	---------------------

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months
----------	-----------