




## V-Gard Visors: Welding (Shades 3 and 5)

|                               |  |
|-------------------------------|--|
| <b>Classification:</b>        | Welding  |
| <b>Market(s):</b>             | Fabrication, steel mills, shipbuilding, construction, open-pit mining, agriculture, oil/gas/petrochemical refineries, rubber manufacturing |
| <b>Application(s):</b>        | Welding, metal pouring, gas soldering, light cutting/brazing, manufacturing, impact and debris   |
| <b>Material:</b>              | Polycarbonate  |
| <b>Color(s):</b>              | Shade 3 IR, green<br>Shade 5 IR, green   |
| <b>Available Styles:</b>      | Molded or Nitrometer   |
| <b>Size:</b>                  | 8" (20.3 cm) x 17" (43.2 cm) x .07" (1.8 mm)   |
| <b>Features:</b>              | Protection from IR, up to Shade 3 or Shade 5, as applicable<br>Impact-rated (Z87+)   |
| <b>Standards<sup>1</sup>:</b> | ANSI/ISEA Z87.1-2010; EN 166 (4-3/3 MSA 1BT39 [shade 3] and 4-5/5 MSA 1BT39 [shade 5]); CSA Z94.3; and AS/NZS 1337                         |
| <b>Certification:</b>         | Third-party by Intertek, INSPEC International Ltd., CSA International and SAI Global Ltd.  |

### Ordering Information

| V-GARD VISORS FOR WELDING APPLICATIONS |   | Part No.  | Product Specifics  |
|--|---|---|--|
|  |   | 10115859<br>   | <ul style="list-style-type: none"> <li>• Shade 3 IR</li> <li>• Visor</li> <li>• Thickness helps prevent pitting and warping from heat or weld spatter</li> </ul>   |
|  |  | 10115860<br> | <ul style="list-style-type: none"> <li>• Shade 3 IR</li> <li>• Nitrometer; for use with V-Gard Retractable or Standard Chin Protectors</li> <li>• Thickness helps prevent pitting and warping from heat or weld spatter</li> </ul> |
|  |  | 10115861<br> | <ul style="list-style-type: none"> <li>• Shade 5 IR</li> <li>• Visor</li> <li>• Thickness helps prevent pitting and warping from heat or weld spatter</li> </ul>   |
|  |  | 10115862<br> | <ul style="list-style-type: none"> <li>• Shade 5 IR</li> <li>• Nitrometer; for use with V-Gard Retractable or Standard Chin Protectors</li> <li>• Thickness helps prevent pitting and warping from heat or weld spatter</li> </ul> |

<sup>1</sup> Standards requirements met by each V-Gard Headgear/V-Gard Visor combination designated on each V-Gard Visor.