

VW49



VW49 - 14" with hang up holes on sides

*Miner49ER Boot Features:*

- CSA M75 Metatarsal Protection
- CSA Z195-09 / ASTM F2413-11 Class #1 Steel toe and plate
- CSA Omega - Electric shock resistant 18kV
- European Standard CE Approved - EN ISO 20345:2011
- Australia New Zealand Standard Approved - AS/NZS 2210.3.2009
- NBR rubber boot with cotton canvas lining
- Nitrile oil, chemical & slip resistant lug sole
- Achilles tendon & ankle protection
- Ultra flexible: Exceeds 150,000 flex rating



SIZE 5 - 15

VW49T



VW49T - 16" Tall

*Miner49ER Tall Boot Features:*

- CSA M75 Metatarsal Protection
- CSA Z195-09 / ASTM F2413-11 Class #1 Steel toe and plate
- CSA Omega - Electric shock resistant 18kV
- European Standard CE Approved - EN ISO 20345:2011
- Australia New Zealand Standard Approved - AS/NZS 2210.3.2009
- NBR rubber boot with cotton canvas lining
- Nitrile oil, chemical & slip resistant lug sole
- Achilles tendon & ankle protection
- Ultra flexible: Exceeds 150,000 flex rating



SIZE 6 - 14

VW42



*MET Guard Boot Features:*

- CSA M75 Metatarsal Protection
- CSA Z195-09 / ASTM F2413-11 Class #1 Steel toe and plate
- Natural rubber with polyester lining
- (VF23) CC5 ergonomic insole included
- Slip resistant lug sole
- Achilles tendon & ankle protection
- 14" height plus 2" nylon cuff to seal out debris & dust
- Snug fit design to provide extra comfort and safety and reduce incidences of ankle roll-over
- Lightweight & flexible, exceeds 80,000 Flex Rating



SIZE 6 - 14