



Product Family
Uvex Genesis S (Slim)








Wrap-around, uni-lens style for superior coverage. Flexible fingers on nosepiece conform to a variety of nasal profiles. Frame and lens are 6% smaller than Genesis to fit slimmer facial profiles.

Learn more about all of our Uvex plano products at uvex.us >

Learn more about our Uvex Rx safety frames at uvexrx.com >



Product Numbers & Ordering Information

Product Numbers	Details
 S3700	Pewter & Black Frame Clear Lens, Ultra-dura Anti-scratch Coating
 S3700X	Pewter & Black Frame Clear Lens, Uvextreme Anti-fog Coating
 S3700D	Pewter & Black Frame Clear Lens, Dura-streme Dual Anti-fog/Anti-Scratch
 S3701	Pewter & Black Frame Gray Lens, Ultra-dura Anti-scratch Coating
 S3701X	Pewter & Black Frame Gray Lens, Uvextreme Anti-fog Coating
 S3702	Pewter & Black Frame Amber Lens, Ultra-dura Anti-scratch Coating
 S3702X	Pewter & Black Frame Amber Lens, Uvextreme Anti-fog Coating

Uvex Genesis S (Slim)



S3703

Pewter & Black Frame
SCT-Reflect 50 Lens, Ultra-dura Anti-scratch Coating



S3704

Pewter & Black Frame
Dark Gray Lens, Ultra-dura Anti-scratch Coating



S3720

Ice Blue Frame
Clear Lens, Ultra-dura Anti-scratch Coating



S3720X

Ice Blue Frame
Clear Lens, Uvextreme Anti-fog Coating



S3720D

Ice Blue Frame
Clear Lens, Dura-streme Dual (Anti-fog/Anti-scratch)



S3721

Ice Blue Frame
Gray Lens, Ultra-dura Anti-scratch Coating



S3721X

Ice Blue Frame
Gray Lens, Uvextreme Anti-fog Coating



S3722

Ice Blue Frame
Amber Lens, Ultra-dura Anti-scratch Coating



S3722X

Ice Blue Frame
Amber Lens, Uvextreme Anti-fog Coating



S3723

Ice Blue Frame
SCT-Reflect 50 Lens, Ultra-dura Anti-scratch Coating



S3724

Ice Blue Frame
Dark Gray Lens, Ultra-dura Anti-scratch Coating



S6610

Replacement Lens
Clear, Ultra-dura Anti-scratch Coating



S6610X

Replacement Lens
Clear, Uvextreme Anti-fog Coating

Uvex Genesis S (Slim)



S6610D

Replacement Lens

Clear, Dura-streme Dual (Anti-fog / Anti-scratch) Coating



S6611

Replacement Lens

Gray, Ultra-dura Anti-scratch Coating



S6611X

Replacement Lens

Gray, Uvextreme Anti-fog Coating



S6612

Replacement Lens

Amber, Ultra-dura Anti-scratch Coating



S6612X

Replacement Lens

Amber, Uvextreme Anti-fog Coating



S6613

Replacement Lens

SCT-Reflect 50, Ultra-dura Anti-scratch Coating



S6614

Replacement Lens

Dark Gray, Ultra-dura Anti-scratch Coating

Packaging Information

Packaging (spectacle) Ind. box, 10/stocker, 200/case Weight (spectacle) 1.125 oz. (31.9g) Ind. Box-Bag Dimensions (spectacle) 6.9 x 2.7" x 2.5" (17.6 x 6.9 x 6.4 cm) " Ind. Box-Bag weight (spectacle) 1.9 oz (54 g) Stocker dimensions (spectacles) 11.8 x 7" x 5.7" (30 x 17.8 x 14.5 cm) " Stocker weight (spectacle) 1.4 lbs (0.65 kg) Master Case Dimensions (Spectacle) 28.9 x 14.5" x 23.6" (73.5 x 36.9 x 60 cm) " Master Case Weight (Spectacle) 31.3 lbs (14.2 kg) Packaging (Repl. Lens) 1 pr./polybag, 10 pr./bag, 200 pr./box Unit Weight (Repl. Lens) 0.05 lb (19.81gm) Ind. Box-Bag dimensions (Repl. Lens) 9 x 5" x 1 7.8" (2.29cm x 12.7cm x 4.76cm) " Ind. Box-Bag weight (Repl. Lens) 0.74 oz. (21g) Stocker dimensions (Repl. Lens) 6 3/4" x 6 3/4" x 2 7/8" (17cm x 17cm x 7cm) Stocker weight (Repl. Lens) 1.10 lbs (.50 kg) Case Dimensions (Repl. Lens) 18.4" x 13.2" x 10" (46.8cm x 33.6cm x 25.4cm) Case Weight (Repl. Lens) 11.03 lb(5kg)

Overview

Key Features

The Genesis S (Slim) is the latest addition to the number one selling eyewear family on the market today. Adding to the comfort, performance and style of the Genesis family, the Genesis S (Slim) offers a 6% smaller frame for workers with slimmer facial profiles. Once again, we've made it easier to fit more workers with the best selling safety eyewear in the world. More faces. More choices. More compliance.

- Wrap-around, 9-base uni-lens style for uncompromised peripheral vision and coverage
- Available with Dura-streme dual coating technology which combines our two best lens coatings — Uvextreme anti-fog on the interior and Ultra-dura anti-scratch on the exterior — for 3x longer lens life*
- Available in Clear, Amber, Gray, Dark Gray, and SCT-Reflect 50 lens tints
- Soft brow guard absorbs and diffuses impact energy
- Soft, flexible "fingers" on nosepiece cMade onform to a variety of facial profiles and minimize slippage
- Padded temple and tips provides all-day comfort
- Economical and easy lens replacement system allows for multiple lens tints and extends the life of the eyewear
- Multiple models in a family offers standardization while offering workers choice
- Lifetime frame guarantee
- Made in USA

Recommended Industries/Use

- Construction
- Food Services
- Pharmaceutical

Hazards

- Abrasion
- Airborne Particulates
- Biohazard
- Impact
- Low Visibility

Regulations

- ANSI Z87+ (High Impact) - Meets ANSI Z87+ (High Impact)
- ANSI Z 87.1/1989, CA 18,819 - Meets ANSI Z 87.1/1989, CA 18,819 (http://www.mte.gov.br/Empregador/segsau/Pesquisa/CA_DET.asp?vNRCAProc=18819&Equipamento=00&NOEquipamento=&Fabricante=00&NOFabricante=)
- CSA Z94.3 - Certified to the requirements of CSA Z94.3 standards
- Military V0 - Meets military V0 ballistic test for impact

Historical Brand

Uvex

Warranty Information

Lifetime frame guarantee

Specifications

Lens overall width

- 5.35" (136 mm) nominal

Lens material

- Polycarbonate

Lens coating

- Ultra-dura®, Anti-Scratch Coating, Uvextreme® AF Anti-Fog Coating, Dura-Streme Technology (Dual Anti-Fog & Anti-Scratch) Coating "

Lens thickness

- 0.067" (1.7 mm) minimum

Lens tints

- Clear, Amber, Gray, Dark Gray, SCT-Reflect 50

Lens base curve

- 9 Base

Replacement lenses or foam available

- Yes

Rx capable

- No

Temple material

- Polycarbonate with elastomer

Temple length

- 4.25" (105 mm) actual, 5.51" (140 mm) fit

Temple set-back

- 3.1" (79 mm)

Temple style

- Spatula (one piece) with elastomer padding

Frame material

- Polycarbonate with elastomer

Frame colors

- Pewter/Black, Ice Blue /Gray

Dielectric frame

- Yes

Training & Proper Use

All products come packaged with instructions and warnings for proper use.

Technical Support

(800) 682-0839, Sperian Protection Americas, Customer Care