



Principal

| | |
|---------------|--------------------|
| Product Type | Démarrateur moteur |
| Product Range | S |
| Starter Type | Non réversible |

Complémentaire

| | |
|------------------------|--|
| NEMA Size | 1 |
| Rated Current | 27 A |
| Number of Poles | 3P |
| Maximum Voltage Rating | 600 V AC |
| Phase | 3 phases |
| Type of Overload | Solid state Motor Logic class 10/20 |
| Horsepower Rating | 7.5 HP at 200 V AC 7.5 HP at 230 V AC 10 HP at 460 V AC 10 HP at 575 V AC |
| SCCR | Circuit-breaker 70 A maximum: 100 kA at 480 V AC Fuse J 60 A maximum: 100 kA at 600 V AC Fuse T 60 A maximum: 100 kA at 600 V AC Fuse RK1 60 A maximum: 100 kA at 600 V AC Fuse RK5 60 A maximum: 100 kA at 600 V AC |
| Coil Voltage | 24 V AC 60 Hz |
| Control Circuit Type | Separate control circuit |
| Control Units | No control units |
| Pilot Light | Without pilot light |
| Auxiliary Contacts | Sans |
| Terminal Type | Borniers à vis-étrier |
| Height | 172,96 mm |

| | |
|-------|-----------|
| Width | 88,90 mm |
| Depth | 107,19 mm |

Environnement

| | |
|----------------|-------------------------|
| Enclosure Type | Not rated (open device) |
| Certifications | Listé UL CSA NEMA |

Emballage

| | |
|---------------------------|----------|
| Poids de l'emballage (Kg) | 1,814 kg |
|---------------------------|----------|

Offre de la durabilité

| | |
|-----------------------|--|
| Régulation REACH | Déclaration REACH |
| Directive RoHS UE | Non conforme |
| Régulation RoHS Chine | Déclaration RoHS pour la Chine Produit en dehors du périmètre RoHS pour la Chine. Déclaration relative aux substances pour votre information. |
| Sans PVC | Oui |

Garantie contractuelle

| | |
|----------|-----------|
| Garantie | 18 months |
|----------|-----------|