

8536SCA3V81FF4T

NEMA Motor Starter, Type S, nonreversing, Size 1, 27A, 10 HP at 460 VAC, 5 kA SCCR, 3 phase, 3 pole, melting alloy, 120 VAC coil, NEMA 12



Principal

| | |
|---------------|------------------|
| Product Type | Démarreur moteur |
| Product Range | S |
| Starter Type | Non réversible |

Complémentaire

| | |
|------------------------|--|
| NEMA Size | 1 |
| Rated Current | 27 A |
| Number of Poles | 3P |
| Maximum Voltage Rating | 600 V AC |
| Phase | 3 phases |
| Type of Overload | Melting alloy 3 |
| Horsepower Rating | 7.5 HP at 200 V AC 7.5 HP at 230 V AC 10 HP at 460 V AC 10 HP at 575 V AC |
| SCCR | Disjoncteur: 5 kA at 600 V AC Fusible: 5 kA at 600 V AC |
| Coil Voltage | 120 V AC 60 Hz circuit secondaire 480 V AC 60 Hz circuit primaire |
| Control Circuit Type | Control circuit transformer |
| Control Units | No control units |
| Pilot Light | Without pilot light |
| Auxiliary Contacts | Sans |
| Other Equipment | 2 fuses (primary), 1 fuse (secondary) |
| Terminal Type | Borniers à vis-étrier |
| Height | 342,90 mm |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|-------|-----------|
| Width | 301,75 mm |
| Depth | 203,20 mm |

Environnement

| | |
|----------------|-------------------------------|
| Enclosure Type | NEMA 12 feuille d'acier peint |
| Certifications | Listé UL CSA NEMA |

Emballage

| | |
|---------------------------|----------|
| Poids de l'emballage (Kg) | 9,226 kg |
|---------------------------|----------|

Offre de la durabilité

| | |
|-----------------------|--|
| Régulation REACH | Déclaration REACH |
| Directive RoHS UE | Non conforme |
| Régulation RoHS Chine | Déclaration RoHS pour la Chine Produit en dehors du périmètre RoHS pour la Chine. Déclaration relative aux substances pour votre information. |
| Sans PVC | Oui |

Garantie contractuelle

| | |
|----------|-----------|
| Garantie | 18 months |
|----------|-----------|