



### Principal

Product	Single Throw Safety Switch
Disconnect Type	Fusible disconnect
Number of Poles	3
Electrical Connection	Cosses
Duty Rating	Renforcé

### Complémentaire

Line Rated Current	600 A
Factory Installed Neutral	Neutral (factory installed)
Mounting Type	Saillie
Voltage Rating	600 V AC/DC
Wire Size	AWG 3/0...500 kcmil copper or aluminium
Puissance moteur hp	150 hp at 480 V AC 50...60 Hz for 3 phases motors conforming to NEC 240.6 400 hp at 480 V AC 50...60 Hz for 3 phases motors conforming to NEC 430.52 200 hp at 600 V AC 50...60 Hz for 3 phases motors conforming to NEC 240.6 500 hp at 600 V AC 50...60 Hz for 3 phases motors conforming to NEC 430.52 50 hp at 250 V DC 50 hp à 600 V DC
Hauteur	1276,35 mm
Largeur	701,80 mm
Profondeur	257,30 mm
Couple de serrage	42.37 N.m (AWG 3/0...500 kcmil)

### Environnement

Certifications	CSA
Enclosure Rating	NEMA 1 Acier galvanisé

## Emballage

Poids de l'emballage (Kg)	90,718 kg
---------------------------	-----------

## Offre de la durabilité

Statut environnemental de l'offre	Produit Green Premium
Régulation REACH	<a href="#">Déclaration REACH</a>
Sans SVHC REACH	Oui
Directive RoHS UE	Conforme <a href="#">Déclaration RoHS UE</a>
Sans mercure	Oui
Information sur les exemptions RoHS	<a href="#">Oui</a>
Régulation RoHS Chine	<a href="#">Déclaration RoHS pour la Chine</a> Produit en dehors du périmètre RoHS pour la Chine. Déclaration relative aux substances pour votre information.
Profil environnemental	<a href="#">Profil environnemental du Produit</a>
Sans PVC	Oui
Présence d'halogènes	Produit avec composants plastiques sans halogènes