

CHU365REI2

400A 3P Type3R 600V Heavy Duty Non-Fusible Safety Switch & Electrical Interlock



Principal

Product	Single Throw Safety Switch
Disconnect Type	Non-fusible disconnect
Number of Poles	3
Electrical Connection	Cosses
Duty Rating	Renforcé

Complémentaire

Line Rated Current	400 A
Factory Installed Neutral	None
Mounting Type	Saillie
Voltage Rating	600 V AC/DC
Wire Size	AWG 1/0...750 kcmil cuivre ou aluminium
Puissance moteur hp	125 hp at 240 V AC 50...60 Hz for 3 phases motors conforming to NEC 430.52 250 hp à 480 V AC 50...60 Hz pour 3 phases moteurs conformément à NEC 430.52 350 hp à 600 V AC 50...60 Hz pour 3 phases moteurs conformément à NEC 430.52 50 hp at 250 V DC 50 hp à 600 V DC
Hauteur	1277,87 mm
Largeur	708,15 mm
Profondeur	257,30 mm
Couple de serrage	62.14 N.m (AWG 1/0...750 kcmil)

Environnement

Certifications	CSA
Enclosure Rating	NEMA 1 Acier galvanisé

Emballage

Poids de l'emballage (Kg)	1,000 kg
---------------------------	----------
