



## Principal

Product	Surge protection device
Range	Surgelogic
Device Short Name	IMA

## Complémentaire

Surge Current	120 kA par phase
Voltage Rating	480 V delta AC
Number of Phases	3 phases
Wiring Configuration	Type 3 fils avec neutre
Connection	Cosses AWG 12...AWG 2 aluminium / cuivre 4 N.m
MCOV	550 V
Nominal Discharge Current	20 kA
SCCR	200 kA
Provided Equipment	Alarm enable/disable switch Diagnostic display Backplane Câbles
Height	155,7 mm
Width	250,4 mm
Depth	92,7 mm

## Environnement

Enclosure Rating	NEMA 1
Standards	UL 1449:ed. 4 CSA C22.2 No 8:1986 UL 96A:ed. 12 UL 1283 IEC 61643-1

## Emballage

Poids de l'emballage (Kg)	3,810 kg
---------------------------	----------

## Offre de la durabilité

Régulation REACH	<a href="#">Déclaration REACH</a>
Directive RoHS UE	Conforme <a href="#">Déclaration RoHS UE</a>
Sans mercure	Oui
Information sur les exemptions RoHS	<a href="#">Oui</a>
Régulation RoHS Chine	<a href="#">Déclaration RoHS pour la Chine</a> Produit en dehors du périmètre RoHS pour la Chine. Déclaration relative aux substances pour votre information.