

Code de commande	Description	Watts (W)	Culot	Volts (V)	Lumens à 120 V (lm)	Vie moyenne (h)	Type de filament	Finition	Qté caisse (int./ext.)
S11									
LHTM : 2 5/16 po (59 mm) LCL : 1 1/2 po (38 mm)									
50789	5S11/CL/1M/E17/130V/STD	5	E17	130	25	1 000	C-7A	Claire	25/500
50143	10S11/CL/1M/E17/130V/STD	10	E17	130	60	1 000	C-7A	Claire	6/120
50165	10S11/F/1M/E17/130V/STD	10	E17	130	60	1 000	C-7A	Givrée	6/120
50786	25S11/CL/1M/E17/130V/STD	25	E17	130	130	1 000	C-7A	Claire	25/500
50123	40S11/CL/1M/E17/130V/STD	40	E17	130	275	1 000	C-7A	Claire	6/120
S14									
LHTM : 2 5/16 po (59 mm) LCL : 1 1/2 po (38 mm)									
59542	11S14/CL/8M/130V/STD	11	E26	130	40	8 000	C-9	Claire	6/24
50147	11S14/CL/3M/130V/STD	11	E26	130	72	3 000	C-9	Claire	25/500
10158	11S14/F/3M/130V/STD	11	E26	130	50	3 000	C-9	Givrée	25/500
T6									
LHTM : 3 1/16 po (78 mm) LCL : 1 9/16 po (40 mm)									
50667	15T6/CL/7.5M/E12/130V/STD	15	E12	130	75	7 500	C-5A	Claire	12/120
50668	15T6/CL/7.5M/E12/145V/STD	15	E12	145	90	7 500	C-5A	Claire	12/120
50675	15T6/CL/5M/E17/130V/STD	15	E17	130	70	5 000	C-5A	Claire	12/120
50676	15T6/CL/7.5M/E17/145V/STD	15	E17	145	90	7 500	C-5A	Claire	12/120
T6.5									
LHTM : 5 13/32 po (137 mm) LCL : 3 5/32 po (80 mm)									
51052	20T6.5/CL/5M/BA15d/130V/STD	20	BA15d	130	115	5 000	C-8	Claire	25/500
50679	20T6.5/F/5M/BA15d/130V/STD	20	BA15d	130	115	5 000	C-8	Givrée	12/120
50677	20T6.5/CL/5M/E17/130V/STD	20	E17	130	115	5 000	C-8	Claire	12/120
50678	20T6.5/F/5M/E17/130V/STD	20	E17	130	115	5 000	C-8	Givrée	12/120
51056	25T6.5/CL/5M/BA15d/125V/STD	25	BA15d	125	180	5 000	C-8	Claire	25/500
50674	25T6.5/CL/7.5M/BA15d/145V/STD	25	BA15d	145	180	7 500	C-8	Claire	12/120
50729	25T6.5/F/7.5M/BA15d/145V/STD	25	BA15d	145	145	7 500	C-8	Givrée	25/500
50671	25T6.5/CL/5M/E12/130V/STD	25	E12	130	135	5 000	C-8	Claire	12/120
50672	25T6.5/CL/7.5M/E12/145V/STD	25	E12	145	180	7 500	C-8	Claire	12/120
50669	25T6.5/CL/5M/E17/130V/STD	25	E17	130	135	5 000	C-8	Claire	12/120
50670	25T6.5/CL/7.5M/E17/145V/STD	25	E17	145	180	7 500	C-8	Claire	12/120
50673	25T6.5/F/7.5M/E17/145V/STD	25	E17	145	180	7 500	C-8	Givrée	25/500
50680	40T6.5/CL/5M/E17/130V/STD	40	E17	130	280	5 000	C-8	Claire	12/120
52191	40T6.5/F/5M/E17/130V/STD	40	E17	130	210	5 000	C-8	Givrée	25/500
T7									
LHTM : 2 5/16 po (59 mm) LCL : 1 5/16 po (33 mm)									
52195	15T7/CL/1.5M/BA15d/120V/STD	15	BA15d	120	100	1 500	C-7A	Claire	25/1 000
52196	15T7/F/1.5M/BA15d/130V/STD	15	BA15d	130	75	1 500	C-7A	Givrée	25/1 000
52192	15T7/CL/1.5M/E12/120V/STD	15	E12	120	100	1 500	C-7A	Claire	25/1 000
52201	25T7/CL/1.5M/E12/130V/STD	25	E12	130	115	1 500	C-7A	Claire	25/1 000
T8									
LHTM : 2 9/16 po (65 mm) LCL : 1 5/8 po (41 mm)									
52198	25T8/CL/1.5M/BA15d/120V/STD	25	BA15d	120	220	1 500	C-7A	Claire	25/1 000
52200	25T8/CL/1.5M/E12/120V/STD	25	E12	120	220	1 500	C-7A	Claire	25/1 000
52197	25T8/CL/1.5M/E17/120V/STD	25	E17	120	220	1 500	C-7A	Claire	25/1 000
T10									
LHTM : 5 po (127 mm) LCL : 2 3/4 po (70 mm)									
50923	15T10/CL/3M/130V/STD	15	E26	130	75	3 000	C-5V	Claire	6/120
50925	25T10/CL/3M/130V/STD	25	E26	130	135	3 000	C-5V	Claire	6/120
50928	25T10/F/3M/130V/STD	25	E26	130	135	3 000	C-5V	Givrée	6/120
50926	40T10/CL/3M/130V/STD	40	E26	130	195	3 000	C-5V	Claire	6/120
50929	40T10/F/3M/130V/STD	40	E26	130	195	3 000	C-5V	Givrée	6/120
50930 ¹	60T10/F/3M/130V/STD	60	E26	130	365	3 000	C-5V	Givrée	6/120
T10 HO									
LHTM : 5 13/32 po (137 mm) LCL : 3 11/32 po (85 mm)									
50149	25T10/CL/3M/HO/130V/STD	25	E26	130	175	3 000	C-8	Claire	6/120
50131	25T10/F/3M/HO/130V/STD	25	E26	130	175	3 000	C-8	Givrée	6/120
50129	40T10/CL/3M/HO/130V/STD	40	E26	130	300	3 000	C-8	Claire	6/120
50132	40T10/F/3M/HO/130V/STD	40	E26	130	300	3 000	C-8	Givrée	6/120

¹ Cet item n'est plus produit conformément à la loi sur les standards en matière d'efficacité énergétique, il sera disponible jusqu'à épuisement des stocks.