

# 8536SEO1V01H30S

NEMA Motor Starter, Type S, nonreversing, Size 3, 90A, 50 HP at 460 VAC, up to 100 kA SCCR, 3 phase, 3 pole, Motor Logic, 24 VAC coil, open



## Principal

Product Type	Démarreur moteur
Product Range	S
Starter Type	Non réversible

## Complémentaire

NEMA Size	3
Rated Current	90 A
Number of Poles	3P
Maximum Voltage Rating	600 V AC
Phase	3 phases
Type of Overload	Solid state Motor Logic class 10/20
Horsepower Rating	25 HP à 200 V AC 30 HP à 230 V AC 50 HP à 460 V AC 50 HP à 575 V AC
SCCR	Disjoncteur 150 A maximum: 100 kA at 480 V AC Fusible J 200 A maximum: 100 kA at 600 V AC Fusible T 200 A maximum: 100 kA at 600 V AC Fusible RK1 200 A maximum: 100 kA at 600 V AC Fusible RK5 200 A maximum: 100 kA at 600 V AC
Coil Voltage	24 V AC 60 Hz
Control Circuit Type	Separate control circuit
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Sans
Terminal Type	Borniers à vis-étrier
Height	281,69 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Width	138,94 mm
Depth	165,10 mm

## Environnement

Enclosure Type	Not rated (open device)
Certifications	Listé UL CSA NEMA

## Emballage

Poids de l'emballage (Kg)	6,804 kg
---------------------------	----------

## Offre de la durabilité

Régulation REACH	<a href="#">Déclaration REACH</a>
Directive RoHS UE	Non conforme
Régulation RoHS Chine	<a href="#">Déclaration RoHS pour la Chine</a> Produit en dehors du périmètre RoHS pour la Chine. Déclaration relative aux substances pour votre information.

## Garantie contractuelle

Garantie	18 months
----------	-----------