

8502SDO2V08

NEMA Contactor, Type S, nonreversing, Size 2, 45A, 25 HP at 575 VAC, 3 phase, up to 100 kA, 3 pole, 208 VAC coil, open



Principal

Product Type	Contacteur
Product Range	8502S
Contactor Type	Non inverseur

Complémentaire

NEMA Size	2
Rated Current	45 A
Number of Poles	3P
Maximum Voltage Rating	600 V AC
Phase	3 phases
Horsepower Rating	10 HP at 200 V AC 15 HP at 230 V AC 25 HP at 460 V AC 25 HP at 575 V AC
SCCR	Disjoncteur 100 A maximum, SCCR: 100 kA at 480 V AC Fusible J 100 A maximum, SCCR: 100 kA at 600 V AC Fusible T 100 A maximum, SCCR: 100 kA at 600 V AC Fusible RK1 100 A maximum, SCCR: 100 kA at 600 V AC Fusible RK5 100 A maximum, SCCR: 100 kA at 600 V AC
Coil Voltage	208 V AC 60 Hz
Control Circuit Type	Common control circuit
Control Units	No control units
Pilot Light	Sans signalisation
Auxiliary Contacts	Sans
Other Equipment	Fusible non fourni
Terminal Type	Borniers à vis-étrier
Height	130,30 mm

Width	109,47 mm
Depth	125,48 mm

Environnemental

Enclosure Type	Not rated (open device)
Certifications	UL listed file E78351 CCN NLDX CSA

Emballage

Poids de l'emballage (Kg)	2,572 kg
Hauteur de l'emballage 1	17,018 cm
Largeur de l'emballage 1	17,018 cm
Longueur de l'emballage 1	23,876 cm

Offre de la durabilité

Régulation REACH	Déclaration REACH
Directive RoHS UE	Non conforme
Régulation RoHS Chine	Déclaration RoHS pour la Chine Produit en dehors du périmètre RoHS pour la Chine. Déclaration relative aux substances pour votre information.

Garantie contractuelle

Garantie	18 months
----------	-----------