

# Lampes DEL



PAR20



PAR30SN



PAR30LN



PAR38



A19



Paquet de 4 A19

Code de commande	Description	Watts (W)	Culot (VCA)	Volts (VCA)	Temp. de couleur (K)	IRC	Vie L70 (h)	Flux lumineux (lm)	Faisceau (°)	CBCP (cd)	Équivalent traditionnel (W)	Capacité de gradation (Oui/Non)	Qté caisse (Int./ext.)
<b>PAR20</b>													
66279 <sup>1</sup>	P20/8W/27K/25/CHOICE/STD	8	E26	120	2 700	≥90	15 000	581	25	1 708	50	Oui	1/12
66280 <sup>1</sup>	P20/8W/27K/40/CHOICE/STD	8	E26	120	2 700	≥90	15 000	572	40	914	50	Oui	1/12
66281 <sup>1</sup>	P20/8W/30K/25/CHOICE/STD	8	E26	120	3 000	≥90	15 000	608	25	1 708	50	Oui	1/12
66282 <sup>1</sup>	P20/8W/30K/40/CHOICE/STD	8	E26	120	3 000	≥90	15 000	605	40	914	50	Oui	1/12
66283 <sup>1</sup>	P20/8W/40K/25/CHOICE/STD	8	E26	120	4 000	≥90	15 000	616	25	1 708	50	Oui	1/12
66284 <sup>1</sup>	P20/8W/40K/40/CHOICE/STD	8	E26	120	4 000	≥90	15 000	652	40	914	50	Oui	1/12
<b>PAR30SN</b>													
66291	P30S/12W/27K/25/CHOICE/STD	12	E26	120	2 700	≥90	15 000	934	25	3 843	75	Oui	1/6
66292	P30S/12W/27K/40/CHOICE/STD	12	E26	120	2 700	≥90	15 000	929	40	1 740	75	Oui	1/6
66293	P30S/12W/30K/25/CHOICE/STD	12	E26	120	3 000	≥90	15 000	965	25	3 843	75	Oui	1/6
66294	P30S/12W/30K/40/CHOICE/STD	12	E26	120	3 000	≥90	15 000	922	40	1 740	75	Oui	1/6
66295	P30S/12W/40K/25/CHOICE/STD	12	E26	120	4 000	≥90	15 000	1 006	25	3 843	75	Oui	1/6
66296	P30S/12W/40K/40/CHOICE/STD	12	E26	120	4 000	≥90	15 000	977	40	1 740	75	Oui	1/6
<b>PAR30LN</b>													
66285	P30L/12W/27K/25/CHOICE/STD	12	E26	120	2 700	≥90	15 000	942	25	4 178	75	Oui	1/6
66286	P30L/12W/27K/40/CHOICE/STD	12	E26	120	2 700	≥90	15 000	935	40	1 813	75	Oui	1/6
66287	P30L/12W/30K/25/CHOICE/STD	12	E26	120	3 000	≥90	15 000	974	25	4 178	75	Oui	1/6
66288	P30L/12W/30K/40/CHOICE/STD	12	E26	120	3 000	≥90	15 000	935	40	1 813	75	Oui	1/6
66289	P30L/12W/40K/25/CHOICE/STD	12	E26	120	4 000	≥90	15 000	1 024	25	4 178	75	Oui	1/6
66290	P30L/12W/40K/40/CHOICE/STD	12	E26	120	4 000	≥90	15 000	996	40	1 813	75	Oui	1/6
<b>PAR38</b>													
66297	P38/16.5W/27K/25/CHOICE/STD	16.5	E26	120	2 700	≥90	15 000	1 360	25	6 067	100	Oui	1/6
66298	P38/16.5W/27K/40/CHOICE/STD	16.5	E26	120	2 700	≥90	15 000	1 398	40	2 527	100	Oui	1/6
66299	P38/16.5W/30K/25/CHOICE/STD	16.5	E26	120	3 000	≥90	15 000	1 419	25	6 067	100	Oui	1/6
66300	P38/16.5W/30K/40/CHOICE/STD	16.5	E26	120	3 000	≥90	15 000	1 355	40	2 527	100	Oui	1/6
66301	P38/16.5W/40K/25/CHOICE/STD	16.5	E26	120	4 000	≥90	15 000	1 548	25	6 067	100	Oui	1/6
66302	P38/16.5W/40K/40/CHOICE/STD	16.5	E26	120	4 000	≥90	15 000	1 510	40	2 527	100	Oui	1/6
<b>A19</b>													
66267 <sup>1,2</sup>	A19/6W/27K/ND/CHOICE/STD	6	E26	120	2 700	≥80	15 000	480	-	-	40	Non	6/48
66268 <sup>1,2</sup>	A19/6W/30K/ND/CHOICE/STD	6	E26	120	3 000	≥80	15 000	480	-	-	40	Non	6/48
66269 <sup>1,2</sup>	A19/9.5W/27K/ND/CHOICE/STD	9.5	E26	120	2 700	≥80	15 000	800	-	-	60	Non	6/48
66270 <sup>1,2</sup>	A19/9.5W/30K/ND/CHOICE/STD	9.5	E26	120	3 000	≥80	15 000	800	-	-	60	Non	6/48
<b>Paquet de 4 A19</b>													
66271 <sup>1,2</sup>	A19/9.5W/27K/ND/CHOICE/STD 4P	9.5	E26	120	2 700	≥80	15 000	800	-	-	60	Non	1/48
66272 <sup>1,2</sup>	A19/9.5W/30K/ND/CHOICE/STD 4P	9.5	E26	120	3 000	≥80	15 000	800	-	-	60	Non	1/48
66273 <sup>1,2</sup>	A19/9.5W/40K/ND/CHOICE/STD 4P	9.5	E26	120	4 000	≥80	15 000	800	-	-	60	Non	1/48
66274 <sup>1,2</sup>	A19/9.5W/50K/ND/CHOICE/STD 4P	9.5	E26	120	5 000	≥80	15 000	800	-	-	60	Non	1/48

Les valeurs de lumen proviennent des essais photométriques  
 Pour connaître la liste complète des gradateurs compatibles et des produits homologués ENERGY STAR,  
 veuillez consulter [www.standardpro.com](http://www.standardpro.com)

