

# 8536SAO12V02H30S

NEMA Motor Starter, Type S, nonreversing, Size 00, 9A, 2 HP at 460 VAC, up to 100 kA SCCR, 3 phase, 3 pole, Motor Logic, 120 VAC coil, open



## Principal

Product Type	Démarrateur moteur
Product Range	S
Starter Type	Non réversible

## Complémentaire

NEMA Size	00
Rated Current	9 A
Number of Poles	3P
Maximum Voltage Rating	600 V AC
Phase	3 phases
Type of Overload	Solid state Motor Logic class 10/20
Horsepower Rating	1.5 HP à 200 V AC 1.5 HP à 230 V AC 2 HP à 460 V AC 2 HP à 575 V AC
SCCR	Circuit-breaker 70 A maximum: 100 kA at 480 V AC Fuse J 60 A maximum: 100 kA at 600 V AC Fuse T 60 A maximum: 100 kA at 600 V AC Fuse RK1 60 A maximum: 100 kA at 600 V AC Fuse RK5 60 A maximum: 100 kA at 600 V AC
Coil Voltage	110 V AC 50 Hz 120 V AC 60 Hz
Control Circuit Type	Separate control circuit
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Sans
Terminal Type	Borniers à vis-étrier

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Height	172,96 mm
Width	88,90 mm
Depth	107,19 mm

## Environnement

Enclosure Type	Not rated (open device)
Certifications	Listé UL CSA NEMA

## Emballage

Poids de l'emballage (Kg)	1,746 kg
Hauteur de l'emballage 1	14,986 cm
Largeur de l'emballage 1	11,938 cm
Longueur de l'emballage 1	20,320 cm

## Offre de la durabilité

Régulation REACH	<a href="#">Déclaration REACH</a>
Directive RoHS UE	Non conforme
Régulation RoHS Chine	<a href="#">Déclaration RoHS pour la Chine</a> Produit en dehors du périmètre RoHS pour la Chine. Déclaration relative aux substances pour votre information.
Sans PVC	Oui

## Garantie contractuelle

Garantie	18 months
----------	-----------