


8536SDO2V02S

NEMA Motor Starter, Type S, nonreversing, Size 2, 45A, 25 HP at 460 VAC, 5 kA SCCR, 2 phase, 4 pole, melting alloy, 120 VAC coil, open



Principal

Product Type	Démarreur moteur
Product Range	S
Starter Type	Non réversible

Complémentaire

NEMA Size	2
Rated Current	45 A
Number of Poles	4P
Maximum Voltage Rating	600 V AC
Phase	2 phases
Type of Overload	Melting alloy 2 Thermal Units
Horsepower Rating	10 HP at 200 V AC 15 HP at 230 V AC 25 HP at 460 V AC 25 HP at 575 V AC
SCCR	Disjoncteur: 5 kA at 600 V AC Fusible: 5 kA at 600 V AC
Coil Voltage	110 V AC 50 Hz 120 V AC 60 Hz
Control Circuit Type	Separate control circuit
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Sans
Terminal Type	Borniers à vis-étrier
Height	198,37 mm
Width	143,00 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Depth	125,48 mm
-------	-----------

Environnement

Enclosure Type	Not rated (open device)
Certifications	Listé UL CSA NEMA

Emballage

Poids de l'emballage (Kg)	3,701 kg
Hauteur de l'emballage 1	16,510 cm
Largeur de l'emballage 1	17,272 cm
Longueur de l'emballage 1	23,114 cm

Offre de la durabilité

Régulation REACH	Déclaration REACH
Directive RoHS UE	Conforme Déclaration RoHS UE
Sans mercure	Oui
Information sur les exemptions RoHS	Oui
Régulation RoHS Chine	Déclaration RoHS pour la Chine Produit en dehors du périmètre RoHS pour la Chine. Déclaration relative aux substances pour votre information.
Sans PVC	Oui

Garantie contractuelle

Garantie	18 months
----------	-----------