

8502SGO2V05

NEMA Contactor, Type S, nonreversing, Size 5, 270A, 200 HP at 575 VAC, 3 phase, up to 100 kA, 3 pole, 380 VAC coil, open



Principal

Product Type	Contacteur
Type	8502S
Control Circuit Type	Common control circuit
Control Circuit Voltage	380 V AC 50 Hz
Contacteur Type	Non inverseur
Current Rating	270 A
Number of Poles	3P
Phase	3 phases
Horsepower Rating	75 HPà 200 V AC 100 HPà 230 V AC 200 HPà 460 V AC 200 HPà 575 V AC
Maximum Voltage Rating	600 V AC
SCCR	Disjoncteur 400 A maximum, SCCR: 100 kA at 480 V AC Fusible J 400 A maximum, SCCR: 100 kA at 600 V AC Fusible T 400 A maximum, SCCR: 100 kA at 600 V AC Fusible RK1 400 A maximum, SCCR: 100 kA at 600 V AC Fusible RK5 400 A maximum, SCCR: 100 kA at 600 V AC
Control Units	No control units
Pilot Light	Sans signalisation
Auxiliary Contacts	Sans
Control Circuit Fusing	Fusible non fourni
Electrical Connection	Borniers à vis-étrier
Enclosure Type	Not rated (open device)
Certifications	UL listed file E78351 CCN NLDX CSA
NEMA Size	5
Height	312,67 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

Depth	222,25 mm
Width	220,22 mm

Emballage

Poids de l'emballage (Kg)	19,051 kg
---------------------------	-----------

Offre de la durabilité

Régulation REACH	Déclaration REACH
Sans SVHC REACH	Oui
Directive RoHS UE	Non conforme
Régulation RoHS Chine	Déclaration RoHS pour la Chine Produit en dehors du périmètre RoHS pour la Chine. Déclaration relative aux substances pour votre information.

Garantie contractuelle

Garantie	18 months
----------	-----------